



Since 1980

PROGRAMMA DI VENDITA SALE PROGRAMME 17

	PISTOLE VARIE • <i>VARIUS GUNS</i> .....	7
	RICAMBI PISTOLE • <i>SPARE PARTS GUNS</i> .....	21
	BLISTER • <i>BLISTER</i> .....	28
	RIDUTTORI DI PRESSIONE - GRUPPI MODULARI • <i>PRESSURE REDUCERS - MODULAR GROUPS</i> .....	29
	RACCORDERIA VARIA • <i>VARIOUS FITTINGS</i> .....	32
	RUBINETTI A SFERA - CORSOIO - IN LINEA • <i>BALL VALVES - SLIDE COCK - IN LINE</i> .....	37
	NIPPLI - RIDUZIONI - MANICOTTI - TAPPI • <i>NIPPLES - REDUCER - SLEEVES - PLUGS</i> .....	38
	RACCORDI STAMPATI IN OTTONE • <i>PRINTED IN BRASS FITTINGS</i> .....	40
	RACCORDI A CALZAMENTO • <i>PUSH-IN FITTINGS</i> .....	42
	RACCORDI AD INNESTO RAPIDO IN OTTONE • <i>BRASS PUSH-IN FITTINGS</i> .....	43
	RACCORDI AD INNESTO RAPIDO IN POLIMERO • <i>POLYMER PUSH-IN FITTINGS</i> .....	45
	RACCORDI AD OGIVA IN OTTONE • <i>BRASS COMPRESSION FITTINGS</i> .....	47
	INNESTI E RUBINETTI RAPIDI A SFERA • <i>QUICK AND FAST BALL VALVES</i> .....	49
	VALVOLE DI RITEGNO E VALVOLE DI SICUREZZA • <i>NON RETARD VALVE AND SAFETY VALVE</i> .....	64
	PRESSOSTATI - RIPARTITORI • <i>PRESSURE SWITCH - MANIFOLDS</i> .....	65
	TUBI GOMMA E SPIRALE • <i>SPIRAL AND RUBBER HOSE</i> .....	68

La Società **O.M.G. di Ghiotto Cav. Giuseppe & C. S.n.c.** venne costituita il 24/10/1978 per iniziativa dei Coniugi Ghiotto Giuseppe e Lovato Maria Assunta sulla base di una specifica esperienza acquisita fin dalla giovinezza. Grazie alla laboriosità ed alla attenzione nel gestire il denaro, i Coniugi poterono contribuire al finanziamento della Società per l'acquisto di uno dei primi lotti di terreno costituenti la zona artigianale del Comune di Brendola. La felice intuizione all'acquisto di quel terreno si confermò nel tempo grazie alla vicinanza del casello autostradale che favorisce le comunicazioni ed i trasporti. Costruirono senza indugi la prima porzione di fabbricato nel quale poterono installare le prime attrezzature acquistate anche grazie alla particolare fiducia dei fornitori e delle banche. Beneficiando delle conoscenze storiche si avviarono i primi rapporti con i clienti che si svilupparono rapidamente grazie alla serietà ed alla precisione dei Fondatori. La nascita di una azienda ha sempre del miracoloso, come lo è quella di un essere umano. Ha del miracoloso quella particolare spinta interiore che trasforma un operaio in imprenditore. Successivamente si unirono i quattro Figli e quindi si può ben dire trattarsi di una azienda cresciuta attorno ad un forte e trainante nucleo familiare, coeso e determinato nella conduzione e nello sviluppo. La gamma degli articoli prodotti andò arricchendosi nel tempo per soddisfare le crescenti richieste della clientela e per la costante ricerca di nuovi settori commerciali. Attualmente si producono un migliaio di articoli che spaziano dalla raccorderia, agli aerografi, ai riduttori di pressione, anche in confezioni blisterate od altre a richiesta dei clienti. L'attività è andata sempre più sviluppandosi sulla base dei rapporti di stima e di fiducia della clientela diretta e di quella aggiunta nel tempo grazie a collaboratori che hanno permesso una presenza in vaste aree anche extra-europee. Attualmente l'attività viene svolta in oltre cinquemila metri quadrati di superficie coperta, con macchinario costantemente all'avanguardia dal punto di vista tecnologico e della sicurezza. La qualità delle lavorazioni, la tempestività nelle consegne e la serietà aziendale contraddistinguono da sempre i Soci, le maestranze e la Società O.M.G. di Ghiotto Cav. Giuseppe & C. S.n.c.


**O.M.G. di Ghiotto Cav. Giuseppe & C. S.n.c.** was established on October 24th, 1978 by Ghiotto Giuseppe and Lovato Maria Assunta, husband and wife, based on specific experience acquired since their youth. Thanks to their hard work and attention to managing the company finances, the husband and wife team was able to buy one of the first plots of land in the industrial area of the Comune of Brendola. This purchase was further enhanced by the presence of the nearby highway tollbooth which favors communication and transport.

Without further delay, they built the first part of the factory where they installed the first equipment they purchased with the added help and trust of their suppliers and banks. The first client relationships began through longtime friendships and developed quickly thanks to the professionalism of the founders, their reliability and attention to detail. The creation of a company, as with a child, is always a somewhat miraculous event. There is something amazing about the internal desire which transforms a worker into an entrepreneur. Thereafter, their four children joined the company. So it is safe to say that this is a company created around a strong and driving family nucleus, that is united and determined in its management and development. The range of item produced has grown over time in order to satisfy increasing client demands and due to a constant search for new business sectors.

Currently, one thousand items are produced ranging from couplings to air guns to pressure reducers, in blister or other packaging on customer request. The company's business activities have continued to grow and develop based on the respect and trust of its direct clients and of its partners, which have over time increased the company's presence, even outside of Europe.

Today the company's business activities are carried out in a more than 5,000 sq.m. covered area, with machinery that is on the cutting edge in terms of technology and safety. The quality of the workmanship, the timeliness of the deliveries and the company's professionalism have always distinguished the partners, workers and O.M.G. di Ghiotto Cav. Giuseppe & C. S.n.c.






Lavorazione fusione pistole  
*Processing of fusion guns*



Banco prova per la verifica dei manometri  
*Test bench to check gauges*



Assemblaggio pistole  
*Assembly of guns*



Lavorazione da barra  
*Bar stock machining*

La O.M.G. di GHIOTTO Cav. Giuseppe & C., grazie alla dotazione di macchine ed attrezzature di lavoro moderne e tecnologicamente avanzate è in grado di garantire elevati standard di precisione e qualità. I materiali sono acquistati da primarie ditte fornitrici e sono generalmente accompagnati dagli appropriati certificati conformi a quanto previsto dalla norma EN 10204. Al termine delle lavorazioni i prodotti finiti vengono collaudati utilizzando appropriati standard interni e per tale motivo la O.M.G. di GHIOTTO è in grado di fornire, su richiesta, le pertinenti certificazioni richieste dalle direttive europee. In particolare vengono fornite:

- **DICHIARAZIONE DI CONFORMITÀ alla direttiva 2001/95/CE sulla sicurezza generale dei prodotti per tutti i prodotti realizzati dalla O.M.G. di GHIOTTO che non rientrano in altre direttive e non sono sottoposti all'obbligo del marchio CE (vedi Fig. A).**
- **DICHIARAZIONE DI CONFORMITÀ alla direttiva 2006/42/CE sulla sicurezza delle macchine per tutti i prodotti progettati e fabbricati dalla O.M.G. di GHIOTTO che sono sottoposti all'obbligo dell'apposizione del marchio CE (vedi Fig. B).**



Fig. A - Fac-simile DICHIARAZIONE DI CONFORMITÀ alla 2001/95/CE  
Fig. A - Copy of DECLARATION OF CONFORMITY with 2001/95/CE



Fig. B - Fac-simile DICHIARAZIONE CE DI CONFORMITÀ alla 2006/42/CE  
Fig. B - Copy of DECLARATION OF CONFORMITY with 2006/42/CE

O.M.G. di Ghiotto Cav. Giuseppe & C., thanks to its modern and technologically advanced machinery and equipment, is able to guarantee high standards of precision and quality. The materials are purchased from primary suppliers companies and are generally accompanied by the appropriate certificate compliance with standard EN 10204. At the end of the manufacturing process, the finished products are tested using appropriate internal standards. As a result, O.M.G. di GHIOTTO is able to provide – upon request – the suitable certification required by the European directives. In particular, the company can provide the following:

- **DECLARATION OF CONFORMITY of directive 2001/95/EC on the general safety of the products for all products made by O.M.G. di GHIOTTO which are not part of other directives and not subject to the EC mark (see Fig. A).**
- **DECLARATION OF CONFORMITY of directive 2006/42/EC on the general safety of the machines for all the products designed and manufactured by O.M.G. di GHIOTTO which are subject to the obligation for affixing of the EC mark (see Fig. B).**

**DICHIARAZIONE DI CONFORMITÀ alla direttiva 2006/42/CE**

sulla sicurezza delle macchine (vedi Fig. D) accompagnata dalla eventuale copia del CERTIFICATO DI APPROVAZIONE CEE DI MODELLO ai sensi delle direttive 71/316/CEE e 86/217/CEE sulle disposizioni comuni agli strumenti di misura e ai manometri per pneumatici di autoveicoli sicurezza delle macchine per i dispositivi di gonfiaggio per autoveicoli per i quali è stata ottenuta l'approvazione CEE di modello dal competente Ministero (vedi Fig. C) e il certificato di idoneità del banco di prova per la verifica dei manometri CEE (vedi Fig. E).

**DECLARATION OF CONFORMITY with directive 2006/42/EC**

on the safety of the machines (see Fig. D) accompanied by any copy of the MODEL EU CERTIFICATE OF APPROVAL according to directives 71/316/EEC and 86/217/EEC on the common provisions for measuring instruments and automotive tire gauges, machine safety, and automotive pumping devices, which have been model EEC approved by the competent Ministry (see Fig. C) and been granted a certificate of approval from the test bench that checks EEC gauges (see Fig. E).





Fig. C - Certificato di approvazione CEE di modello ART. 83  
Fig. C - Model EC Certificate of Approval, ART. 83



Fig. D - Fac-simile DICHIARAZIONE CE DI CONFORMITÀ alla 2006/42/CE  
Fig. D - Copy of DECLARATION OF CONFORMITY with 2006/42/EC

Fig. E - Fac-simile CERTIFICAZIONE BANCO DI PROVA  
Fig. E - Copy of TEST BENCH CERTIFICATION

## TIPI DI ATTACCHI • TYPES OF COUPLING



## CONFEZIONI KIT KITS

### ART. 70I



#### CONFEZIONE KIT IN SCATOLA:

- 1 AEROGRAFO INFERIORE KG 1 (ART. 62)
- 1 PISTOLA DI GONFIAGGIO (ART. 53)
- 1 PISTOLA DI LAVAGGIO (ART. 55)
- 1 PISTOLA DI SOFFIAGGIO (ART. 50)
- 1 SPIRALE RACCORDATA  
BAIONETTA-BAIONETTA (ART. 00)

#### BOX CONTENTS:

- 1 SPRAY-GUN LOWER TANK KG 1 (ART. 62)
- 1 INFLATING GUN (ART. 53)
- 1 WASHING GUN (ART. 55)
- 1 BLOW GUN (ART. 50)
- 1 BAYONET-BAYONET SPIRAL HOSE (ART. 00)

\*SPECIFICARE IL TIPO DI ATTACCO • SPECIFY TYPE OF COUPLING

### ART. 70S



#### CONFEZIONE KIT IN SCATOLA:

- 1 AEROGRAFO SUPERIORE KG 0,5 (ART. 61)
- 1 PISTOLA DI GONFIAGGIO (ART. 53)
- 1 PISTOLA DI LAVAGGIO (ART. 55)
- 1 PISTOLA DI SOFFIAGGIO (ART. 50)
- 1 SPIRALE RACCORDATA  
BAIONETTA-BAIONETTA (ART. 00)

#### BOX CONTENTS:

- 1 SPRAY-GUN UPPER TANK KG 0,5 (ART. 61)
- 1 INFLATING GUN (ART. 53)
- 1 WASHING GUN (ART. 55)
- 1 BLOW GUN (ART. 50)
- 1 BAYONET-BAYONET SPIRAL HOSE (ART. 00)

\*SPECIFICARE IL TIPO DI ATTACCO • SPECIFY TYPE OF COUPLING

### ART. 70BI



#### CONFEZIONE KIT IN BLISTER:

- 1 AEROGRAFO INFERIORE KG 1 (ART. 62)
- 1 PISTOLA DI GONFIAGGIO (ART. 53)
- 1 PISTOLA DI LAVAGGIO (ART. 55)
- 1 PISTOLA DI SOFFIAGGIO (ART. 50)
- 1 SPIRALE RACCORDATA  
BAIONETTA-BAIONETTA (ART. 00)

#### BLISTER CONTENTS:

- 1 SPRAY-GUN LOWER TANK KG 1 (ART. 62)
- 1 INFLATING GUN (ART. 53)
- 1 WASHING GUN (ART. 55)
- 1 BLOW GUN (ART. 50)
- 1 BAYONET-BAYONET SPIRAL HOSE (ART. 00)

\*SPECIFICARE IL TIPO DI ATTACCO • SPECIFY TYPE OF COUPLING

### ART. 70BS



#### CONFEZIONE KIT IN BLISTER:

- 1 AEROGRAFO SUPERIORE KG 0,5 (ART. 61)
- 1 PISTOLA DI GONFIAGGIO (ART. 53)
- 1 PISTOLA DI LAVAGGIO (ART. 55)
- 1 PISTOLA DI SOFFIAGGIO (ART. 50)
- 1 SPIRALE RACCORDATA  
BAIONETTA-BAIONETTA (ART. 00)

#### BLISTER CONTENTS:

- 1 SPRAY-GUN UPPER TANK KG 0,5 (ART. 61)
- 1 INFLATING GUN (ART. 53)
- 1 WASHING GUN (ART. 55)
- 1 BLOW GUN (ART. 50)
- 1 BAYONET-BAYONET SPIRAL HOSE (ART. 00)

\*SPECIFICARE IL TIPO DI ATTACCO • SPECIFY TYPE OF COUPLING

## ART. 50



**PISTOLA DI SOFFIAGGIO**  
IN ALLUMINIO, TRATTAMENTO  
BRILLANTATO  
Consumo aria a 6 bar: 180 l/min

**ALUMINIUM BLOW GUN**  
BRILLANT TREATMENT  
Air consumption at 6 bar:  
180 l/min

## ART. 50SV



**PISTOLA DI SOFFIAGGIO**  
IN ALLUMINIO, TRATTAMENTO  
SABBIATO VERNICIATO  
Consumo aria a 6 bar: 180 l/min

**ALUMINIUM BLOW GUN**  
SANDED PAINT TREATMENT  
Air consumption at 6 bar:  
180 l/min

## ART. 50V



**PISTOLA DI SOFFIAGGIO**  
VENTURI  
IN ALLUMINIO, TRATTAMENTO  
BRILLANTATO  
Consumo aria a 6 bar: 180 l/min

**ALUMINIUM VENTURI**  
BLOW GUN  
BRILLANT TREATMENT  
Air consumption at 6 bar:  
180 l/min

## ART. 50VSV



**PISTOLA DI SOFFIAGGIO**  
VENTURI  
IN ALLUMINIO, TRATTAMENTO  
SABBIATO VERNICIATO  
Consumo aria a 6 bar: 180 l/min

**ALUMINIUM VENTURI**  
BLOW GUN  
SANDED PAINT TREATMENT  
Air consumption at 6 bar:  
180 l/min

## ART. 51



**PISTOLA DI SOFFIAGGIO CANNA LUNGA**  
IN ALLUMINIO, TRATTAMENTO BRILLANTATO  
Consumo aria a 6 bar: 180 l/min  
Lunghezza canna: 190 mm \*

\*A richiesta disponibile con lunghezza canna 100 mm

**ALUMINIUM BLOW GUN WITH LONG NOZZLE**  
BRILLANT TREATMENT

Air consumption at 6 bar: 180 l/min - Length nozzle: 190 mm \*

\*On demand available with length nozzle: 100 mm

## ART. 51SV



**PISTOLA DI SOFFIAGGIO CANNA LUNGA**  
IN ALLUMINIO, TRATTAMENTO SABBIATO VERNICIATO  
Consumo aria a 6 bar: 180 l/min  
Lunghezza canna: 190 mm \*

\*A richiesta disponibile con lunghezza canna 100 mm

**ALUMINIUM BLOW GUN WITH LONG NOZZLE**  
SANDED PAINT TREATMENT

Air consumption at 6 bar: 180 l/min - Length nozzle: 190 mm \*

\*On demand available with length nozzle: 100 mm

## ART. 68



**PISTOLA DI SOFFIAGGIO**  
ANTINFORTUNISTICA  
IN ALLUMINIO, TRATTAMENTO  
BRILLANTATO  
Consumo aria a 6 bar: 180 l/min

**ALUMINIUM SAFETY**  
BLOW GUN  
BRILLANT TREATMENT  
Air consumption at 6 bar:  
180 l/min

## ART. 68SV



**PISTOLA DI SOFFIAGGIO**  
ANTINFORTUNISTICA  
IN ALLUMINIO, TRATTAMENTO  
SABBIATO VERNICIATO  
Consumo aria a 6 bar: 180 l/min

**ALUMINIUM SAFETY**  
BLOW GUN  
SANDED PAINT TREATMENT  
Air consumption at 6 bar:  
180 l/min



## ART. 51A



**PISTOLA DI SOFFIAGGIO PER STAMPI**  
IN ALLUMINIO,  
TRATTAMENTO BRILLANTATO  
Consumo aria a 6 bar: 180 l/min  
Lunghezza canna: 190 mm

**ALUMINIUM BLOW GUN WITH BENT NOZZLE**  
BRILLANT TREATMENT  
Air consumption at 6 bar: 180 l/min  
Length nozzle: 190 mm


## ART. 51ASV



**PISTOLA DI SOFFIAGGIO PER STAMPI**  
IN ALLUMINIO, TRATTAMENTO SABBBIATO VERNICIATO  
Consumo aria a 6 bar: 180 l/min  
Lunghezza canna: 190 mm

**ALUMINIUM BLOW GUN WITH BENT NOZZLE**  
SANDED PAINT TREATMENT  
Air consumption at 6 bar: 180 l/min  
Length nozzle: 190 mm

## ART. 52



**PISTOLA DI GONFIAGGIO**  
IN ALLUMINIO, TRATTAMENTO BRILLANTATO  
Lunghezza tubo: 300 mm

**ALUMINIUM INFLATING GUN**  
BRILLANT TREATMENT  
Length hose: 300 mm

## ART. 52SV



**PISTOLA DI GONFIAGGIO**  
IN ALLUMINIO, TRATTAMENTO SABBBIATO VERNICIATO  
Lunghezza tubo: 300 mm

**ALUMINIUM INFLATING GUN**  
SANDED PAINT TREATMENT  
Length hose: 300 mm

## ART. 50B



**PISTOLA DI SOFFIAGGIO PROFESSIONALE CON REGOLAZIONE ARIA PROGRESSIVA**  
Consumo aria a 6 bar: 260 l/min  
Lunghezza canna: 110 mm \*  
\*A richiesta disponibile con lunghezza canna: 300 mm e 350 mm

**PROFESSIONAL BLOWING GUN PROVIDED WITH LEVER FOR THE ADJUSTMENT OF THE AIR FLOW**  
Air consumption at 6 bar: 260 l/min  
Length nozzle: 110 mm \*  
\*On demand available with length nozzle: 300 mm and 350 mm

## ART. 50BS



**PISTOLA DI SOFFIAGGIO PROFESSIONALE CON REGOLAZIONE ARIA PROGRESSIVA CON SPIRALE 4 m**  
Consumo aria a 6 bar: 260 l/min  
Lunghezza canna: 110 mm \*  
\*A richiesta disponibile con lunghezza canna: 300 mm e 350 mm

**PROFESSIONAL BLOWING GUN PROVIDED WITH LEVER FOR THE ADJUSTMENT OF THE AIR FLOW WITH 4 m SPIRAL HOSE**  
Air consumption at 6 bar: 260 l/min  
Length nozzle: 110 mm \*  
\*On demand available with length nozzle: 300 mm and 350 mm

## ART. 50BG



**PISTOLA DI SOFFIAGGIO PROFESSIONALE CON REGOLAZIONE ARIA PROGRESSIVA**  
Consumo aria a 6 bar: 260 l/min  
Lunghezza canna: 110 mm \*  
\*A richiesta disponibile con lunghezza canna: 300 mm e 350 mm

**PROFESSIONAL BLOWING GUN PROVIDED WITH LEVER FOR THE ADJUSTMENT OF THE AIR FLOW**  
Air consumption at 6 bar: 260 l/min  
Length nozzle: 110 mm \*  
\*On demand available with length nozzle: 300 mm and 350 mm

## ART. 50BGR



**PISTOLA DI SOFFIAGGIO PROFESSIONALE CON REGOLAZIONE ARIA PROGRESSIVA**  
Consumo aria a 6 bar: 260 l/min  
Lunghezza canna: 110 mm \*  
\*A richiesta disponibile con lunghezza canna: 300 mm e 350 mm

**PROFESSIONAL BLOWING GUN PROVIDED WITH LEVER FOR THE ADJUSTMENT OF THE AIR FLOW**  
Air consumption at 6 bar: 260 l/min  
Length nozzle: 110 mm \*  
\*On demand available with length nozzle: 300 mm and 350 mm



**ART. 53**

PISTOLA DI GONFIAGGIO IN ALLUMINIO CON MANOMETRO Ø 63 E TESTINA IN **ZAMA** ART.56ZM

ALUMINIUM INFLATING GUN WITH Ø 63 GAUGE AND **ZAMA** HEAD ART.56ZM

TRATTAMENTO BRILLANTATO  
Pressione manometro max: 0-12 bar  
Lunghezza tubo: 300 mm

**ART. 53OT**

PISTOLA DI GONFIAGGIO IN ALLUMINIO CON MANOMETRO Ø 63 E TESTINA IN **OTTONE** ART.56OT

ALUMINIUM INFLATING GUN WITH Ø 63 GAUGE AND **BRASS** HEAD ART.56OT

**ART. 53W**

PISTOLA DI GONFIAGGIO IN ALLUMINIO CON MANOMETRO "**WIKA**" Ø 63 E TESTINA IN **ZAMA** ART.56ZM

ALUMINIUM INFLATING GUN WITH Ø 63 GAUGE "**WIKA**" AND **ZAMA** HEAD ART.56ZM

BRILLANT TREATMENT  
Max pressure gauge: 0-12 bar  
Length hose: 300 mm

**ART. 53WOT**

PISTOLA DI GONFIAGGIO IN ALLUMINIO CON MANOMETRO "**WIKA**" Ø 63 E TESTINA IN **OTTONE** ART.56OT

ALUMINIUM INFLATING GUN WITH Ø 63 GAUGE "**WIKA**" AND **BRASS** HEAD ART.56OT



**ART. 53SV**

PISTOLA DI GONFIAGGIO IN ALLUMINIO CON MANOMETRO Ø 63 E TESTINA IN **ZAMA** ART.56ZM

ALUMINIUM INFLATING GUN WITH Ø 63 GAUGE AND **ZAMA** HEAD ART.56ZM

TRATTAMENTO SABBBIATO VERNICIATO  
Pressione manometro max: 0-12 bar  
Lunghezza tubo: 300 mm

**ART. 53OTSV**

PISTOLA DI GONFIAGGIO IN ALLUMINIO CON MANOMETRO Ø 63 E TESTINA IN **OTTONE** ART.56OT

ALUMINIUM INFLATING GUN WITH Ø 63 GAUGE AND **BRASS** HEAD ART.56OT

**ART. 53WSV**

PISTOLA DI GONFIAGGIO IN ALLUMINIO CON MANOMETRO "**WIKA**" Ø 63 E TESTINA IN **ZAMA** ART.56ZM

ALUMINIUM INFLATING GUN WITH Ø 63 GAUGE "**WIKA**" AND **ZAMA** HEAD ART.56M

SANDED PAINT TREATMENT  
Max pressure gauge: 0-12 bar  
Length hose: 300 mm

**ART. 53WOTSV**

PISTOLA DI GONFIAGGIO IN ALLUMINIO CON MANOMETRO "**WIKA**" Ø 63 E TESTINA IN **OTTONE** ART.56OT

ALUMINIUM INFLATING GUN WITH Ø 63 GAUGE "**WIKA**" AND **BRASS** HEAD ART.56OT



**ART. 53VG**

PISTOLA DI GONFIAGGIO IN ALLUMINIO CON MANOMETRO Ø 63 E VALVOLA PER RUOTE GEMELLATE

ALUMINIUM INFLATING GUN WITH Ø 63 GAUGE AND CHUCK FOR TWINS TYRES

TRATTAMENTO BRILLANTATO  
Pressione manometro max: 0-12 bar  
Lunghezza tubo: 750 mm

**ART. 53WVG**

PISTOLA DI GONFIAGGIO IN ALLUMINIO CON MANOMETRO "**WIKA**" Ø 63 E VALVOLA PER RUOTE GEMELLATE

ALUMINIUM INFLATING GUN WITH Ø 63 GAUGE "**WIKA**" AND CHUCK FOR TWINS TYRES

BRILLANT TREATMENT  
Max pressure gauge: 0-12 bar  
Length hose: 750 mm



**ART. 53DG**

PISTOLA DI GONFIAGGIO IN ALLUMINIO CON MANOMETRO DIGITALE Ø 63 E TESTINA IN **OTTONE** ART.56OT IN SCATOLA

ALUMINIUM INFLATING GUN WITH Ø 63 DIGITAL GAUGE AND **BRASS** HEAD ART.56OT IN BOX

TRATTAMENTO SABBBIATO VERNICIATO  
Pressione manometro max: 0-12 bar  
Lunghezza tubo: 300 mm

SANDED PAINT TREATMENT  
Max pressure gauge: 0-12 bar  
Length hose: 300 mm

**ART. 63**

PISTOLA DI GONFIAGGIO PROFESSIONALE  
IN ALLUMINIO CON MANOMETRO Ø 80  
E TESTINA IN OTTONE ART.560T

PROFESSIONAL ALUMINIUM INFLATING GUN  
WITH Ø 80 GAUGE AND BRASS HEAD ART.560T

TRATTAMENTO BRILLANTATO  
Pressione manometro max: 0-12 bar  
Lunghezza tubo: 750 mm



**ART. 63W**

PISTOLA DI GONFIAGGIO PROFESSIONALE  
IN ALLUMINIO CON MANOMETRO "WIKA"  
Ø 80 E TESTINA IN OTTONE ART.560T

PROFESSIONAL ALUMINIUM INFLATING GUN  
WITH Ø 80 GAUGE "WIKA" AND BRASS HEAD  
ART.560T

BRILLANT TREATMENT  
Max pressure gauge: 0-12 bar  
Length hose: 750 mm

**ART. 64**

PISTOLA DI GONFIAGGIO PROFESSIONALE  
IN ALLUMINIO CON MANOMETRO Ø 63  
E TESTINA IN OTTONE ART.560T

PROFESSIONAL ALUMINIUM INFLATING GUN  
WITH Ø 63 GAUGE AND  
BRASS HEAD ART.560T

TRATTAMENTO BRILLANTATO  
Pressione manometro max: 0-12 bar  
Lunghezza tubo: 750 mm



**ART. 64W**

PISTOLA DI GONFIAGGIO PROFESSIONALE  
IN ALLUMINIO CON MANOMETRO "WIKA"  
Ø 63 E TESTINA IN OTTONE ART.560T

PROFESSIONAL ALUMINIUM INFLATING GUN  
WITH Ø 63 GAUGE "WIKA" AND  
BRASS HEAD ART.560T

BRILLANT TREATMENT  
Max pressure gauge: 0-12 bar  
Length hose: 750 mm

**ART. 63SV**

PISTOLA DI GONFIAGGIO PROFESSIONALE  
IN ALLUMINIO CON MANOMETRO Ø 80  
E TESTINA IN OTTONE ART.560T

PROFESSIONAL ALUMINIUM INFLATING GUN  
WITH Ø 80 GAUGE AND  
BRASS HEAD ART.560T

TRATTAMENTO SABBBIATO VERNICIATO  
Pressione manometro max: 0-12 bar  
Lunghezza tubo: 750 mm



**ART. 63WSV**

PISTOLA DI GONFIAGGIO PROFESSIONALE  
IN ALLUMINIO CON MANOMETRO "WIKA"  
Ø 80 E TESTINA IN OTTONE ART.560T

PROFESSIONAL ALUMINIUM INFLATING GUN  
WITH Ø 80 GAUGE "WIKA" AND  
BRASS HEAD ART.560T

SANDED PAINT TREATMENT  
Max pressure gauge: 0-12 bar  
Length hose: 750 mm

**ART. 64SV**

PISTOLA DI GONFIAGGIO PROFESSIONALE  
IN ALLUMINIO CON MANOMETRO Ø 63  
E TESTINA IN OTTONE ART.560T

PROFESSIONAL ALUMINIUM INFLATING GUN  
WITH Ø 63 GAUGE AND BRASS HEAD ART.560T

TRATTAMENTO SABBIATO VERNICIATO  
Pressione manometro max: 0-12 bar  
Lunghezza tubo:750 mm



**ART. 64WSV**

PISTOLA DI GONFIAGGIO PROFESSIONALE  
IN ALLUMINIO CON MANOMETRO "WIKA"  
Ø 63 E TESTINA IN OTTONE ART.560T

PROFESSIONAL ALUMINIUM INFLATING GUN  
WITH Ø 63 GAUGE "WIKA" AND BRASS HEAD  
ART.560T

SANDED PAINT TREATMENT  
Max pressure gauge: 0-12 bar  
Length hose: 750 mm

**ART. 63VG**

PISTOLA DI GONFIAGGIO PROFESSIONALE  
IN ALLUMINIO CON MANOMETRO Ø 80  
E VALVOLA PER RUOTE GEMELLATE

PROFESSIONAL ALUMINIUM INFLATING GUN  
WITH Ø 80 GAUGE  
AND CHUCK FOR TWINS TYRES

TRATTAMENTO BRILLANTATO  
Pressione manometro max: 0-12 bar  
Lunghezza tubo:750 mm



**ART. 63WVG**

PISTOLA DI GONFIAGGIO PROFESSIONALE  
IN ALLUMINIO CON MANOMETRO "WIKA"  
Ø 80 E VALVOLA PER RUOTE GEMELLATE

PROFESSIONAL ALUMINIUM INFLATING GUN  
WITH Ø 80 GAUGE "WIKA" AND  
CHUCK FOR TWINS TYRES

BRILLANT TREATMENT  
Max pressure gauge: 0-12 bar  
Length hose: 750 mm

**ART. 64VG**

PISTOLA DI GONFIAGGIO PROFESSIONALE  
IN ALLUMINIO CON MANOMETRO Ø 63  
E VALVOLA PER RUOTE GEMELLATE

PROFESSIONAL ALUMINIUM INFLATING GUN  
WITH Ø 63 GAUGE AND  
CHUCK FOR TWINS TYRES

TRATTAMENTO BRILLANTATO  
Pressione manometro max: 0-12 bar  
Lunghezza tubo:750 mm



**ART. 64WVG**

PISTOLA DI GONFIAGGIO PROFESSIONALE  
IN ALLUMINIO CON MANOMETRO "WIKA"  
Ø 63 E VALVOLA PER RUOTE GEMELLATE

PROFESSIONAL ALUMINIUM INFLATING GUN  
WITH Ø 63 GAUGE "WIKA" AND  
CHUCK FOR TWINS TYRES

BRILLANT TREATMENT  
Max pressure gauge: 0-12 bar  
Length hose: 750 mm


## ART. 54

### MANOMETRO PROVA PRESSIONE

Pressione manometro max: 0-12 bar  
Lunghezza tubo: 300 mm

#### PRESSURE GAUGE


Max pressure gauge: 0-12 bar  
Length hose: 300 mm



## ART. 53HOBBY

### PISTOLA DI GONFIAGGIO CON KIT 4 PEZZI:

A- Ciclo  
B- Pneumatico  
C- Pallone  
D- Canotto  
TRATTAMENTO BRILLANTATO  
Pressione manometro max: 0-12 bar  
Lunghezza tubo: 130 mm



#### INFLATING GUN WITH KIT 4 PIECES:

A- For cycle  
B- For car tyre  
C- For balls  
D- For rubber boats  
BRILLANT TREATMENT  
Max pressure gauge: 0-12 bar  
Length hose: 130 mm

## ART. 54ZM

## ART. 54OT

### MANOMETRO PROVA PRESSIONE CON TESTINA GONFIAGGIO IN ZAMA (ART.54ZM) O IN OTTONE (ART.54OT)

Pressione manometro max: 0-12 bar  
Lunghezza tubo: 300 mm

PRESSURE GAUGE WITH ZAMA INFLATING HEAD (ART.54ZM) OR BRASS INFLATING HEAD (ART.54OT)  
Max pressure gauge: 0-12 bar  
Length hose: 300 mm



## ART. 54SC

### MANOMETRO PROVA PRESSIONE CON PULSANTE SCARICO ARIA

Pressione manometro max: 0-12 bar  
Lunghezza tubo: 300 mm

PRESSURE GAUGE WITH BOTTON FOR AIR DISCHARGE  
Max pressure gauge: 0-12 bar  
Length hose: 300 mm



Assemblaggio pistole  
Assembly of guns

ART. 83



**PISTOLA DI GONFIAGGIO PROFESSIONALE, IN ALLUMINIO, OMOLOGATA SECONDO DIRETTIVA 86/217/CEE CON MANOMETRO Ø 80 TRATTAMENTO BRILLANTATO**  
 Pressione manometro max: 0 - 10 bar  
 Lunghezza tubo: 1000 mm  
 IN SCATOLA, CON CERTIFICATO DI COLLAUDO

**PROFESSIONAL ALUMINIUM INFLATING GUN APPROVED ACCORDING TO THE DIRECTIVE 86/217/EEC WITH Ø 80 GAUGE BRILLANT TREATMENT**  
 Max pressure gauge: 0 - 10 bar  
 Length hose: 1000 mm  
 IN BOX, WITH TEST CERTIFICATE



INCOGNOMORFA  
\*FERTILE  
\*AERODIFFRATTI  
\*IMMUTABILI  
\*TEST PER ARIA COMPRESSA

35  
Anniversario  
1980-2015

**PRODOTTO IN ITALIA.**  
PRODUCT IN ITALY  
 MADE IN ITALY/CHINA/CEE

**ATTESTATO DI COLLAUDO**  
**ACCURACY CERTIFICATE**  
**ATTESTATION DE VERIFICATION**

<ul style="list-style-type: none"> <li>- Riferimenti: - Reference - Référence</li> <li>- Dispositivo: - Device - Type d'appareil</li> <li>- Pressione di utilizzo: - Pressure range - Pression d'utilisation</li> <li>- Certificato d'approvazione di modello: - Model approval certificate - Certificat d'approbation de modèle</li> <li>- Pressione misurata: - Measured pressures - Valeurs vérifiées</li> <li>- Tolleranza di errore: - Maximum permissible errors - Tolérances</li> <li>- Sistema di controllo: - Master gauge - Manomètre de contrôle</li> </ul>	<p>Direttiva Europea 86/217/EEC                  European Directive 86/217/EEC                  Directive Européenne 86/217/EEC</p> <p>Norma EN 12645:1998                  Norm EN 12645:1998                  EN 12645:1998 Norme</p> <p>Sistema di gonfiaggio ART. 83                  Inflator gauge                  Pistolet de gonflage</p> <p><b>0,7 ÷ 10 bar</b></p> <p>09.04.01.13 del 01.07.2009</p> <p><b>4 - 6 - 9 bar</b></p> <table border="1" style="width: 100%; text-align: center;"> <tr> <td>± 0,08 bar fino a 4 bar inclusi up to 4 bar included jusqu'à 4 bar inclus</td> <td>± 0,16 bar da 4 a 6 bar inclusi from 4 to 6 bar included de 4 à 6 bar inclus</td> <td>± 0,25 bar da 6 a 10 bar inclusi from 6 to 10 bar included de 6 à 10 bar inclus</td> </tr> </table> <p>errore inferiore a 1/4 della massima tolleranza consentita. Collaudo effettuato con sistema di calibrazione che include Banco Prova Manometri cod. 03070901 e n. 3 strumenti con certificato di taratura SIT 24 n. 0426-SP-08, n. 0427-SP-08, n. 0428-SP-08 del 27.03.2008.                  error less than 1/4 of the maximum permissible errors. Accuracy checked via a system of calibration which includes our Dead Weight Pressure Test cod. 03070901 and n. 3 gauges with calibration certificate SIT 24 n. 0426-SP-08, n. 0427-SP-08, n. 0428-SP-08 of the 27.03.2008.                  tolérance inférieure à 1/4 des erreurs maximales. Exactitude vérifiée par un système d'étalonnage qui comprend un Banc à Poids cod. 03070901 et n. 3 manomètres avec certificat de calibration SIT 24 n. 0426-SP-08, n. 0427-SP-08, n. 0428-SP-08 du 27.03.2008.</p>	± 0,08 bar fino a 4 bar inclusi up to 4 bar included jusqu'à 4 bar inclus	± 0,16 bar da 4 a 6 bar inclusi from 4 to 6 bar included de 4 à 6 bar inclus	± 0,25 bar da 6 a 10 bar inclusi from 6 to 10 bar included de 6 à 10 bar inclus
± 0,08 bar fino a 4 bar inclusi up to 4 bar included jusqu'à 4 bar inclus	± 0,16 bar da 4 a 6 bar inclusi from 4 to 6 bar included de 4 à 6 bar inclus	± 0,25 bar da 6 a 10 bar inclusi from 6 to 10 bar included de 6 à 10 bar inclus		

- Numero di serie del dispositivo:  
 - Inflator gauge serial number  
 - Numéro de série de l'appareil

Questo attestato garantisce la verifica iniziale del dispositivo. Si raccomanda di controllare periodicamente i dispositivi in servizio.  
 This certificate guarantees initial gauge accuracy. It is recommended to periodically check gauges in service.  
 Ce certificat garantit l'exactitude en sortie d'usine. Il est recommandé de contrôler périodiquement les appareils en service.

**Data:** 16.03.2017      **Operatore n.:** 03  
**Date:**                      **Operator n.:**                      **Opérateur n.**

Il responsabile del controllo  
 Controlleur  
 Le responsable de l'étalonnage

**O.M.G.** di Ghiotto Cav. Giuseppe & c. s.n.c. - Via A. Pacinotti, 18 - 36040 BRENDOLA (VI) ITALIA  
 Cod. Fisc. e P. IVA: IT 00646680249 - C.C.I.A.A. n. 143938 - Iscr. Trib. VI n. 9306 Reg. Soc Numero Mecc. VI 033295  
 Tel: +39 0444 400671 - Fax +39 0444 401025 - E-mail [info@omgonline.it](mailto:info@omgonline.it) - [www.omgonline.it](http://www.omgonline.it)

ART. 73



**PISTOLA DI GONFIAGGIO IN ALLUMINIO, OMOLOGATA SECONDO DIRETTIVA 86/217/CEE CON MANOMETRO Ø 63 TRATTAMENTO BRILLANTATO**  
 Pressione manometro max: 0 - 10 bar  
 Lunghezza tubo: 300 mm

**ALUMINIUM INFLATING GUN APPROVED ACCORDING TO THE DIRECTIVE 86/217/EEC WITH Ø 63 GAUGE BRILLANT TREATMENT**  
 Max pressure gauge: 0 - 10 bar  
 Length hose: 300 mm



INCOGNOMORFA  
\*FERTILE  
\*AERODIFFRATTI  
\*IMMUTABILI  
\*TEST PER ARIA COMPRESSA

35  
Anniversario  
1980-2015

**PRODOTTO IN ITALIA.**  
PRODUCT IN ITALY  
 MADE IN ITALY/CHINA/CEE

**ATTESTATO DI COLLAUDO**  
**ACCURACY CERTIFICATE**  
**ATTESTATION DE VERIFICATION**

<ul style="list-style-type: none"> <li>- Riferimenti: - Reference - Référence</li> <li>- Dispositivo: - Device - Type d'appareil</li> <li>- Pressione di utilizzo: - Pressure range - Pression d'utilisation</li> <li>- Certificato d'approvazione di modello: - Model approval certificate - Certificat d'approbation de modèle</li> <li>- Pressione misurata: - Measured pressures - Valeurs vérifiées</li> <li>- Tolleranza di errore: - Maximum permissible errors - Tolérances</li> <li>- Sistema di controllo: - Master gauge - Manomètre de contrôle</li> </ul>	<p>Direttiva Europea 86/217/EEC                  European Directive 86/217/EEC                  Directive Européenne 86/217/EEC</p> <p>Norma EN 12645:1998                  Norm EN 12645:1998                  EN 12645:1998 Norme</p> <p>Sistema di gonfiaggio ART. 73                  Inflator gauge                  Pistolet de gonflage</p> <p><b>0,7 ÷ 10 bar</b></p> <p>CEE 03 04.01.010 del 22.05.2013</p> <p><b>3,5 - 6 - 8 bar</b></p> <table border="1" style="width: 100%; text-align: center;"> <tr> <td>± 0,08 bar fino a 4 bar inclusi up to 4 bar included jusqu'à 4 bar inclus</td> <td>± 0,16 bar da 4 a 6 bar inclusi from 4 to 6 bar included de 4 à 6 bar inclus</td> <td>± 0,25 bar da 6 a 10 bar inclusi from 6 to 10 bar included de 6 à 10 bar inclus</td> </tr> </table> <p>errore inferiore a 1/4 della massima tolleranza consentita. Collaudo effettuato con sistema di calibrazione che include Banco Prova Manometri cod. 03070901 e n. 3 strumenti con certificato di taratura SIT 24 n. 0426-SP-08, n. 0427-SP-08, n. 0428-SP-08 del 27.03.2008.                  error less than 1/4 of the maximum permissible errors. Accuracy checked via a system of calibration which includes our Dead Weight Pressure Test cod. 03070901 and n. 3 gauges with calibration certificate SIT 24 n. 0426-SP-08, n. 0427-SP-08, n. 0428-SP-08 of the 27.03.2008.                  tolérance inférieure à 1/4 des erreurs maximales. Exactitude vérifiée par un système d'étalonnage qui comprend un Banc à Poids cod. 03070901 et n. 3 manomètres avec certificat de calibration SIT 24 n. 0426-SP-08, n. 0427-SP-08, n. 0428-SP-08 du 27.03.2008.</p>	± 0,08 bar fino a 4 bar inclusi up to 4 bar included jusqu'à 4 bar inclus	± 0,16 bar da 4 a 6 bar inclusi from 4 to 6 bar included de 4 à 6 bar inclus	± 0,25 bar da 6 a 10 bar inclusi from 6 to 10 bar included de 6 à 10 bar inclus
± 0,08 bar fino a 4 bar inclusi up to 4 bar included jusqu'à 4 bar inclus	± 0,16 bar da 4 a 6 bar inclusi from 4 to 6 bar included de 4 à 6 bar inclus	± 0,25 bar da 6 a 10 bar inclusi from 6 to 10 bar included de 6 à 10 bar inclus		

- Numero di serie del dispositivo:  
 - Inflator gauge serial number  
 - Numéro de série de l'appareil

Questo attestato garantisce la verifica iniziale del dispositivo. Si raccomanda di controllare periodicamente i dispositivi in servizio.  
 This certificate guarantees initial gauge accuracy. It is recommended to periodically check gauges in service.  
 Ce certificat garantit l'exactitude en sortie d'usine. Il est recommandé de contrôler périodiquement les appareils en service.

**Data:** 15.03.2017      **Operatore n.:** 01  
**Date:**                      **Operator n.:**                      **Opérateur n.**

Il responsabile del controllo  
 Controlleur  
 Le responsable de l'étalonnage

**O.M.G.** di Ghiotto Cav. Giuseppe & c. s.n.c. - Via A. Pacinotti, 18 - 36040 BRENDOLA (VI) ITALIA  
 Cod. Fisc. e P. IVA: IT 00646680249 - C.C.I.A.A. n. 143938 - Iscr. Trib. VI n. 9306 Reg. Soc Numero Mecc. VI 033295  
 Tel: +39 0444 400671 - Fax +39 0444 401025 - E-mail [info@omgonline.it](mailto:info@omgonline.it) - [www.omgonline.it](http://www.omgonline.it)

**ART. 55**

**PISTOLA DI LAVAGGIO  
IN ALLUMINIO CON SERBATOIO  
IN ACCIAIO KG 1**  
TRATTAMENTO BRILLANTATO  
Consumo d'aria: 200/250 l/min  
6/8 bar

**ALUMINIUM WASHING GUN  
WITH STEEL TANK KG 1**  
BRILLANT TREATMENT  
Air consumption : 200/250 l/min  
6/8 bar



**ART. 55SV**

**PISTOLA DI LAVAGGIO  
IN ALLUMINIO CON SERBATOIO  
IN ACCIAIO DA KG 1**  
TRATTAMENTO  
SABBIATO VERNICIATO  
Consumo d'aria: 200/250 l/min  
6/8 bar

**ALUMINIUM WASHING GUN  
WITH STEEL TANK KG 1**  
SANDED PAINT TREATMENT  
Air consumption : 200/250 l/min  
6/8 bar



**ART. 57**

**PISTOLA DI LAVAGGIO  
IN ALLUMINIO CON SERBATOIO  
IN ALLUMINIO KG 1**  
TRATTAMENTO BRILLANTATO  
Consumo d'aria: 200/250 l/min  
6/8 bar

**ALUMINIUM WASHING GUN  
WITH ALUMINIUM  
TANK KG 1**  
BRILLANT TREATMENT  
Air consumption : 200/250 l/min  
6/8 bar



**ART. 57SV**

**PISTOLA DI LAVAGGIO  
IN ALLUMINIO  
CON SERBATOIO  
IN ALLUMINIO KG 1**  
TRATTAMENTO  
SABBIATO VERNICIATO  
Consumo d'aria: 200/250 l/min  
6/8 bar

**ALUMINIUM WASHING GUN  
WITH ALUMINIUM  
TANK KG 1**  
SANDED PAINT TREATMENT  
Air consumption : 200/250 l/min  
6/8 bar



**ART. 58**

**PISTOLA DI LAVAGGIO  
IN ALLUMINIO CON SERBATOIO  
KG 1 E COPERCHIO  
TUTTO IN ALLUMINIO**  
TRATTAMENTO BRILLANTATO  
Consumo d'aria: 200/250 l/min  
6/8 bar

**ALUMINIUM WASHING GUN  
WITH TANK KG 1 AND TOP  
ALL IN ALUMINUM**  
BRILLANT TREATMENT  
Air consumption : 200/250 l/min  
6/8 bar



**ART. 58SV**

**PISTOLA DI LAVAGGIO  
IN ALLUMINIO CON SERBATOIO  
KG 1 E COPERCHIO  
TUTTO IN ALLUMINIO**  
TRATTAMENTO  
SABBIATO VERNICIATO  
Consumo d'aria: 200/250 l/min  
6/8 bar

**ALUMINIUM WASHING GUN  
WITH TANK KG 1 AND TOP  
ALL IN ALUMINUM**  
SANDED PAINT TREATMENT  
Air consumption : 200/250 l/min  
6/8 bar



**ART. 66**

**PISTOLA ANTIROMBO  
IN ALLUMINIO  
CON SERBATOIO KG 1**  
TRATTAMENTO BRILLANTATO  
Consumo d'aria: 200/250 l/min  
6/8 bar

**ALUMINIUM SPRAY GUN  
FOR UNDERBODY PAINTS  
TREATMENTS WITH TANK KG 1**  
BRILLANT TREATMENT  
Air consumption : 200/250 l/min  
6/8 bar



**ART. 66SV**

**PISTOLA ANTIROMBO  
IN ALLUMINIO  
CON SERBATOIO KG 1**  
TRATTAMENTO  
SABBIATO VERNICIATO  
Consumo d'aria: 200/250 l/min  
6/8 bar

**ALUMINIUM SPRAY GUN  
FOR UNDERBODY PAINTS  
TREATMENTS WITH TANK KG 1**  
SANDED PAINT TREATMENT  
Air consumption : 200/250 l/min  
6/8 bar



**ART. 67**



**PISTOLA ANTIROMBO  
IN ALLUMINIO  
SENZA SERBATOIO**  
TRATTAMENTO BRILLANTATO  
Consumo d'aria: 200/250 l/min  
6/8 bar

**ALUMINIUM SPRAY GUN  
FOR UNDERBODY PAINTS  
TREATMENTS WITHOUT TANK**  
BRILLANT TREATMENT  
Air consumption : 200/250 l/min  
6/8 bar


**ART. 67SV**



**PISTOLA ANTIROMBO  
IN ALLUMINIO  
SENZA SERBATOIO**  
TRATTAMENTO  
SABBIATO VERNICIATO  
Consumo d'aria: 200/250 l/min  
6/8 bar

**ALUMINIUM SPRAY GUN  
FOR UNDERBODY PAINTS  
TREATMENTS WITHOUT TANK**  
SANDED PAINT TREATMENT  
Air consumption : 200/250 l/min  
6/8 bar

**ART. 67T**



**PISTOLA ANTIROMBO  
IN ALLUMINIO  
CON TUBO FLESSIBILE**  
TRATTAMENTO BRILLANTATO  
Consumo d'aria: 200/250 l/min  
6/8 bar

**ALUMINIUM SPRAY GUN  
FOR UNDERBODY PAINTS  
TREATMENTS  
WITH FLEXIBLE HOSE**  
BRILLANT TREATMENT

Air consumption : 200/250 l/min  
6/8 bar

**ART. 67TSV**



**PISTOLA ANTIROMBO  
IN ALLUMINIO  
CON TUBO FLESSIBILE**  
TRATTAMENTO  
SABBIATO VERNICIATO  
Consumo d'aria: 200/250 l/min  
6/8 bar

**ALUMINIUM SPRAY GUN  
FOR UNDERBODY PAINTS  
TREATMENTS  
WITH FLEXIBLE HOSE**

SANDED PAINT TREATMENT  
Air consumption : 200/250 l/min  
6/8 bar

**ART. 67TB**



**ART. 67TBSV**



**ART. 65**



**PISTOLA PER SABBIATURA  
IN ALLUMINIO  
CON SERBATOIO KG 1**  
TRATTAMENTO BRILLANTATO  
Consumo d'aria: 200/250 l/min  
6/8 bar

**ALUMINIUM SANDBLASTING  
GUN WITH TANK KG 1**  
BRILLANT TREATMENT  
Air consumption : 200/250 l/min  
6/8 bar

**ART. 65SV**



**PISTOLA PER SABBIATURA  
IN ALLUMINIO  
CON SERBATOIO KG 1**  
TRATTAMENTO  
SABBIATO VERNICIATO  
Consumo d'aria: 200/250 l/min  
6/8 bar

**ALUMINIUM SANDBLASTING  
GUN WITH TANK KG 1**  
SANDED PAINT TREATMENT  
Air consumption : 200/250 l/min  
6/8 bar

**ART. 65A**



**PISTOLA PER SABBIATURA  
IN ALLUMINIO CON TUBO DI  
PESCAGGIO 1 M**  
TRATTAMENTO BRILLANTATO  
Consumo d'aria: 200/250 l/min  
6/8 bar

**ALUMINIUM SANDBLASTING  
GUN WITH HOSE 1 M**  
BRILLANT TREATMENT  
Air consumption : 200/250 l/min  
6/8 bar

**ART. 65ASV**



**PISTOLA PER SABBIATURA  
IN ALLUMINIO CON TUBO DI  
PESCAGGIO 1 M**  
TRATTAMENTO  
SABBIATO VERNICIATO  
Consumo d'aria: 200/250 l/min  
6/8 bar

**ALUMINIUM SANDBLASTING  
GUN WITH HOSE 1 M**  
SANDED PAINT TREATMENT  
Air consumption : 200/250 l/min  
6/8 bar



## ART. 92B



APRE/CHIUDE ACQUA  
OPEN/CLOSE WATER

**PISTOLA ARIA-ACQUA  
IN ALLUMINIO CON SERBATOIO  
PER LO SHAMPOO KG 1**  
TRATTAMENTO BRILLANTATO  
Consumo d'aria: 200/250 l/min  
6/8 bar

**ALUMINIUM WATER-BLOW GUN  
WITH TANK FOR SHAMPOO KG 1**  
BRILLANT TREATMENT  
Air consumption : 200/250 l/min  
6/8 bar

## ART. 92BSV



APRE/CHIUDE ACQUA  
OPEN/CLOSE WATER

**PISTOLA ARIA-ACQUA  
IN ALLUMINIO CON SERBATOIO  
PER LO SHAMPOO KG 1**  
TRATTAMENTO SABBBIATO  
VERNICIATO  
Consumo d'aria: 200/250 l/min  
6/8 bar

**ALUMINIUM WATER-BLOW GUN  
WITH TANK FOR SHAMPOO KG 1**  
SANDED PAINT TREATMENT  
Air consumption : 200/250 l/min  
6/8 bar

## ART. 92A



APRE/CHIUDE ACQUA  
OPEN/CLOSE WATER

**PISTOLA ARIA-ACQUA  
IN ALLUMINIO  
CON ATTACCO GARDEN**  
TRATTAMENTO BRILLANTATO  
Consumo d'aria: 200/250 l/min  
6/8 bar

**ALUMINIUM WATER-BLOW GUN  
WITH FITTING GARDEN**  
BRILLANT TREATMENT  
Air consumption : 200/250 l/min  
6/8 bar

## ART. 92ASV



APRE/CHIUDE ACQUA  
OPEN/CLOSE WATER

**PISTOLA ARIA-ACQUA  
IN ALLUMINIO  
CON ATTACCO GARDEN**  
TRATTAMENTO SABBBIATO  
VERNICIATO  
Consumo d'aria: 200/250 l/min  
6/8 bar

**ALUMINIUM WATER-BLOW GUN  
WITH FITTING GARDEN**  
SANDED PAINT TREATMENT  
Air consumption : 200/250 l/min  
6/8 bar

## ART. 92



APRE/CHIUDE ACQUA  
OPEN/CLOSE WATER

**PISTOLA ARIA-ACQUA  
IN ALLUMINIO  
CON RESCA Ø 12**  
TRATTAMENTO BRILLANTATO  
Consumo d'aria: 200/250 l/min  
6/8 bar

**ALUMINIUM WATER-BLOW GUN  
WITH FITTING Ø 12**  
BRILLANT TREATMENT  
Air consumption : 200/250 l/min  
6/8 bar

## ART. 92SV



APRE/CHIUDE ACQUA  
OPEN/CLOSE WATER

**PISTOLA ARIA-ACQUA  
IN ALLUMINIO  
CON RESCA Ø 12**  
TRATTAMENTO SABBBIATO  
VERNICIATO  
Consumo d'aria: 200/250 l/min  
6/8 bar

**ALUMINIUM WATER-BLOW GUN  
WITH FITTING Ø 12**  
SANDED PAINT TREATMENT  
Air consumption : 200/250 l/min  
6/8 bar

## ART. 91P



**PISTOLA IN ALLUMINIO PER  
SCHIUMA POLIURETANO**  
TRATTAMENTO BRILLANTATO

**ALUMINIUM GUN  
FOR POLYURETHANE FOAM**  
BRILLANT TREATMENT

## ART. 91PSV



**PISTOLA IN ALLUMINIO PER  
SCHIUMA POLIURETANO**  
TRATTAMENTO SABBBIATO  
VERNICIATO

**ALUMINIUM GUN  
FOR POLYURETHANE FOAM**  
SANDED PAINT TREATMENT

## ART. 61



**PISTOLA DI VERNICIATURA  
IN ALLUMINIO CON SERBATOIO  
SUPERIORE IN ALLUMINIO  
KG 0,5 O KG 1**  
TRATTAMENTO BRILLANTATO  
Ø UGELLI DISPONIBILI:  
1-1,2-1,5-1,8-2-2,5-3  
Pressione max d'esercizio: 4-8 bar  
Consumo d'aria: 140/240 l/min

**ALUMINIUM SPRAY GUN WITH  
ALUMINIUM UPPER TANK  
KG 0,5 OR KG 1**  
BRILLANT TREATMENT  
Ø NOZZLES AVAILABLE:  
1-1,2-1,5-1,8-2-2,5-3  
Max working pressure: 4-8 bar  
Air consumption : 140/240 l/min

## ART. 61SV



**PISTOLA DI VERNICIATURA  
IN ALLUMINIO CON SERBATOIO  
SUPERIORE IN ALLUMINIO  
KG 0,5 O KG 1**  
TRATTAMENTO SABBBIATO VERNICIATO  
Ø UGELLI DISPONIBILI:  
1-1,2-1,5-1,8-2-2,5-3  
Pressione max d'esercizio: 4-8 bar  
Consumo d'aria: 140/240 l/min

**ALUMINIUM SPRAY GUN WITH  
ALUMINIUM UPPER TANK  
KG 0,5 OR KG 1**  
SANDED PAINT TREATMENT  
Ø NOZZLES AVAILABLE:  
1-1,2-1,5-1,8-2-2,5-3  
Max working pressure: 4-8 bar  
Air consumption : 140/240 l/min

## ART. 61A



**PISTOLA DI VERNICIATURA  
IN ALLUMINIO CON SERBATOIO  
SUPERIORE IN NYLON KG 0,5**  
TRATTAMENTO BRILLANTATO  
Ø UGELLI DISPONIBILI:  
1-1,2-1,5-1,8-2-2,5-3  
Pressione max d'esercizio: 4-8 bar  
Consumo d'aria: 140/240 l/min

**ALUMINIUM SPRAY GUN WITH  
NYLON UPPER TANK KG 0,5**  
BRILLANT TREATMENT  
Ø NOZZLES AVAILABLE:  
1-1,2-1,5-1,8-2-2,5-3  
Max working pressure: 4-8 bar  
Air consumption : 140/240 l/min

## ART. 61ASV



**PISTOLA VERNICIATURA  
IN ALLUMINIO CON SERBATOIO  
SUPERIORE IN NYLON KG 0,5**  
TRATTAMENTO  
SABBBIATO VERNICIATO  
Ø UGELLI DISPONIBILI:  
1-1,2-1,5-1,8-2-2,5-3  
Pressione max d'esercizio: 4-8 bar  
Consumo d'aria: 140/240 l/min

**ALUMINIUM SPRAY GUN WITH  
NYLON UPPER TANK KG 0,5**  
SANDED PAINT TREATMENT  
Ø NOZZLES AVAILABLE:  
1-1,2-1,5-1,8-2-2,5-3  
Max working pressure: 4-8 bar  
Air consumption : 140/240 l/min

## ART. 62



**PISTOLA DI VERNICIATURA  
IN ALLUMINIO CON SERBATOIO  
INFERIORE KG 1**  
TRATTAMENTO BRILLANTATO  
Ø UGELLI DISPONIBILI:  
1-1,2-1,5-1,8-2-2,5-3  
Pressione max d'esercizio: 4-8 bar  
Consumo d'aria: 140/240 l/min

**ALUMINIUM SPRAY GUN WITH  
LOWER TANK KG 1**  
BRILLANT TREATMENT  
Ø NOZZLES AVAILABLE:  
1-1,2-1,5-1,8-2-2,5-3  
Max working pressure: 4-8 bar  
Air consumption : 140/240 l/min

## ART. 62SV



**PISTOLA DI VERNICIATURA  
IN ALLUMINIO CON SERBATOIO  
INFERIORE KG 1**  
TRATTAMENTO  
SABBBIATO VERNICIATO  
Ø UGELLI DISPONIBILI:  
1-1,2-1,5-1,8-2-2,5-3  
Pressione max d'esercizio: 4-8 bar  
Consumo d'aria: 140/240 l/min

**ALUMINIUM SPRAY GUN WITH  
LOWER TANK KG 1**  
SANDED PAINT TREATMENT  
Ø NOZZLES AVAILABLE:  
1-1,2-1,5-1,8-2-2,5-3  
Max working pressure: 4-8 bar  
Air consumption : 140/240 l/min

## ART. 62A



**PISTOLA DI VERNICIATURA  
IN ALLUMINIO CON SERBATOIO  
INFERIORE KG 1 E COPERCHIO IN  
ALLUMINIO**  
TRATTAMENTO BRILLANTATO  
Ø UGELLI DISPONIBILI:  
1-1,2-1,5-1,8-2-2,5-3  
Pressione max d'esercizio: 4-8 bar  
Consumo d'aria: 140/240 l/min

**ALUMINIUM SPRAY GUN  
WITH LOWER TANK KG 1  
ALL ALUMINIUM**  
BRILLANT TREATMENT  
Ø NOZZLES AVAILABLE:  
1-1,2-1,5-1,8-2-2,5-3  
Max working pressure: 4-8 bar  
Air consumption : 140/240 l/min

**ART. MASTER 2800**



**PISTOLA DI VERNICIATURA PROFESSIONALE IN ALLUMINIO CON SERBATOIO KG 1 IN SCATOLA**  
TRATTAMENTO BRILLANTATO  
Ø UGELLI DISPONIBILI: 1,2-1,5-1,8-2-2,5  
Pressione max d'esercizio: 4-8 bar  
Consumo d'aria: 140/240 l/min

**PROFESSIONAL ALUMINIUM SPRAY GUN WITH BAYONET LOCK TANK KG 1, IN BOX**  
BRILLANT TREATMENT  
Ø NOZZLES AVAILABLE: 1,2-1,5-1,8-2-2,5  
Max working pressure: 4-8 bar  
Air consumption : 140/240 l/min

**ART. PROFI MASTER 2800**



**PISTOLA DI VERNICIATURA PROFESSIONALE IN ALLUMINIO CON SERBATOIO KG 1 IN SCATOLA**  
TRATTAMENTO SABBIAIA CROMATA  
Ø UGELLI DISPONIBILI: 1,2-1,5-1,8-2-2,5  
Pressione max d'esercizio: 4-8 bar  
Consumo d'aria: 140/240 l/min

**PROFESSIONAL ALUMINIUM SPRAY GUN WITH BAYONET LOCK TANK KG 1, IN BOX**  
SANDED CHROME TREATMENT  
Ø NOZZLES AVAILABLE: 1,2-1,5-1,8-2-2,5  
Max working pressure: 4-8 bar  
Air consumption : 140/240 l/min

**ART. 2900**



**PISTOLA DI VERNICIATURA IN ALLUMINIO CON SERBATOIO CHIUSURA AUTOCLAVE KG 1 TRATTAMENTO BRILLANTATO**  
Ø UGELLI DISPONIBILI: 1-1,2-1,5-1,8-2-2,5-3  
Pressione max d'esercizio: 4-8 bar  
Consumo d'aria: 140/240 l/min

**ALUMINIUM SPRAY GUN WITH CLAMP TYPE TANK KG 1**  
BRILLANT TREATMENT  
Ø NOZZLES AVAILABLE: 1-1,2-1,5-1,8-2-2,5-3  
Max working pressure: 4-8 bar  
Air consumption : 140/240 l/min

**ART. MASTER 2900**



**PISTOLA DI VERNICIATURA IN ALLUMINIO CON SERBATOIO CHIUSURA AUTOCLAVE KG 1 IN SCATOLA**  
TRATTAMENTO SABBIAIA CROMATA  
Ø UGELLI DISPONIBILI: 1-1,2-1,5-1,8-2-2,5-3  
Pressione max d'esercizio: 4-8 bar  
Consumo d'aria: 140/240 l/min

**ALUMINIUM SPRAY GUN WITH CLAMP TYPE TANK KG 1 IN BOX**  
SANDED CHROME TREATMENT  
Ø NOZZLES AVAILABLE: 1-1,2-1,5-1,8-2-2,5-3  
Max working pressure: 4-8 bar  
Air consumption : 140/240 l/min

**ART. MASTER 3000**



**PISTOLA DI VERNICIATURA PROFESSIONALE IN ALLUMINIO CON SERBATOIO CHIUSURA AUTOCLAVE KG 1, IN SCATOLA**  
TRATTAMENTO BRILLANTATO  
Ø UGELLI DISPONIBILI: 1,2-1,5-1,8-2-2,5  
Pressione max d'esercizio: 4-8 bar  
Consumo d'aria: 140/240 l/min

**PROFESSIONAL ALUMINIUM SPRAY GUN WITH CLAMP TYPE TANK KG 1, IN BOX**  
BRILLANT TREATMENT  
Ø NOZZLES AVAILABLE: 1,2-1,5-1,8-2-2,5  
Max working pressure: 4-8 bar  
Air consumption : 140/240 l/min

**ART. PROFI MASTER 3000**



**PISTOLA DI VERNICIATURA PROFESSIONALE IN ALLUMINIO CON SERBATOIO CHIUSURA AUTOCLAVE KG 1, IN SCATOLA**  
TRATTAMENTO SABBIAIA CROMATA  
Ø UGELLI DISPONIBILI: 1,2-1,5-1,8-2-2,5  
Pressione max d'esercizio: 4-8 bar  
Consumo d'aria: 140/240 l/min

**PROFESSIONAL ALUMINIUM SPRAY GUN WITH CLAMP TYPE TANK KG 1, IN BOX**  
SANDED CHROME TREATMENT  
Ø NOZZLES AVAILABLE: 1,2-1,5-1,8-2-2,5  
Max working pressure: 4-8 bar  
Air consumption : 140/240 l/min

**ART. MASTER 3100**



**PISTOLA DI VERNICIATURA PROFESSIONALE IN ALLUMINIO CON SERBATOIO SUPERIORE IN NYLON KG 0,5, IN SCATOLA**  
TRATTAMENTO BRILLANTATO  
Ø UGELLI DISPONIBILI: 1,2-1,5-1,8-2-2,5  
Pressione max d'esercizio: 4-8 bar  
Consumo d'aria: 140/240 l/min

**PROFESSIONAL ALUMINIUM SPRAY GUN WITH NYLON UPPER TANK KG 0,5, IN BOX**  
BRILLANT TREATMENT  
Ø NOZZLES AVAILABLE: 1,2-1,5-1,8-2-2,5  
Max working pressure: 4-8 bar  
Air consumption : 140/240 l/min

**ART. PROFI MASTER 3100**



**PISTOLA DI VERNICIATURA PROFESSIONALE IN ALLUMINIO CON SERBATOIO SUPERIORE IN NYLON KG 0,5, IN SCATOLA**  
TRATTAMENTO SABBIAIA CROMATA  
Ø UGELLI DISPONIBILI: 1,2-1,5-1,8-2-2,5  
Pressione max d'esercizio: 4-8 bar  
Consumo d'aria: 140/240 l/min

**PROFESSIONAL ALUMINIUM SPRAY GUN WITH NYLON UPPER TANK KG 0,5, IN BOX**  
SANDED CHROME TREATMENT  
Ø NOZZLES AVAILABLE: 1,2-1,5-1,8-2-2,5  
Max working pressure: 4-8 bar  
Air consumption : 140/240 l/min

## ART. 6162



Ø UGELLI DISPONIBILI:  
Ø NOZZLES AVAILABLE:

1	2
1,2	2,5
1,5	3
1,8	

RICAMBI PER PISTOLE DI  
VERNICIATURA ART.  
61/61A/62/62A/2900

Composta da: duse - ugello - spillo

SPARE PARTS FOR SPRAY GUN  
ART. 61/61A/62/62A/2900

Composed by: duse - nozzle - pin

## ART. 2700



Ø UGELLI DISPONIBILI:  
Ø NOZZLES AVAILABLE:

1,2	2
1,5	2,5
1,8	

RICAMBI PER PISTOLE  
VERNICIATURA PROFESSIONALE  
ART. PROFIMASTER E MASTER

SPARE PARTS FOR  
PROFESSIONAL SPRAY GUN  
ART. PROFIMASTER AND MASTER

## ART. 3500



PISTOLA DI VERNICIATURA IN  
ALLUMINIO PER VERNICI AD ALTA  
DENSITÀ (all'acqua) SERBATOIO  
SUPERIORE KG 0,6, IN SCATOLA  
TRATTAMENTO SABBIA CROMATA  
Ø UGELLI DISPONIBILI: 1,8 - 2  
Pressione max d'esercizio: 4-8 bar  
Consumo d'aria: 140/240 l/min

ALUMINUM SPRAY GUN FOR  
HIGH DENSITY PAINT (water)  
KG 0,6 UPPER TANK, IN BOX  
SANDED CHROME TREATMENT  
Ø NOZZLES AVAILABLE: 1,8 - 2  
Max working pressure: 4-8 bar  
Air consumption : 140/240 l/min



## ART. 51R



**CANNA LUNGA RICAMBIO**  
PER ART. 51  
Lunghezza canna: 190 mm\*  
\*A richiesta disponibile con lunghezza canna:  
100 mm

**LONG NOZZLE SPARE**  
FOR ART. 51  
Length nozzle: 190 mm\*  
\*On demand available with length nozzle:  
100 mm

## ART. 50BR



**BECCUCCIO SILENZIATORE**  
PER ART. 50B

**SILENCER NOZZLE**  
FOR ART. 50B

## ART. 50R



**BECCUCCIO DI RICAMBIO**  
PER PISTOLA DI SOFFIAGGIO 1/4  
PER ART. 50

**NOZZLE 1/4 OF SPARE**  
FOR BLOW GUN  
FOR ART. 50

## ART. 55R



**BECCUCCIO PISTOLA**  
DI LAVAGGIO  
PER ART. 55/57/58

**WASHING GUN NOZZLE**  
FOR ART. 55/57/58

## ART. 65R



**UGELLO DI RICAMBIO**  
PER PISTOLA SABBIAIATURA  
PER ART. 65

**SPARE NOZZLE FOR**  
BLASTING GUN  
FOR ART. 65

## ART. 50VR



**BECCUCCIO VENTURI 1/4**

**VENTURI NOZZLE 1/4**

## Art. 68R



**BECCUCCIO DI RICAMBIO**  
PER PISTOLA  
ANTINFORTUNISTICA  
PER ART. 68

**SPARE NOZZLE FOR SAFETY BLOW**  
GUN  
FOR ART. 68

## Art. 300F



**VALVOLA GONFIAGGIO**  
RUOTE GEMELLATE  
ATTACCO FEMMINA 1/4

**INFLATING VALVE FOR TWINS**  
TYRES FEMALE THREAD 1/4

## ART. 300MF



**VALVOLA GONFIAGGIO**  
RUOTE GEMELLATE  
CON MANICO  
FILETTO FEMMINA 1/4

**INFLATING VALVE FOR TWINS**  
TYRES WITH HANDLE  
FEMALE THREAD 1/4

## ART. 300R



**VALVOLA GONFIAGGIO**  
RUOTE GEMELLATE  
ATTACCO PORTAGOMMA

- Ø 6
- Ø 8

**INFLATING VALVE FOR TWINS**  
TYRES WITH HOSE CONNECTION

- Ø 6
- Ø 8

## ART. 310F



VALVOLA GONFIAGGIO  
RUOTE GEMELLATE  
CON AGGANCIO PER ART. 56ZM  
E ART. 56OT

INFLATING VALVE FOR TWINS  
TYRES WITH HOOK  
FOR ART. 56ZM AND ART. 56OT

## ART. 53DZ ART. 53DOT



TUBO COMPLETO RICAMBIO  
PER PISTOLA DI GONFIAGGIO  
CON TESTINA IN ZAMA (ART.53DZ)  
O IN OTTONE (ART.53DOT)  
Lunghezza tubo: 300, 500, 750,  
1000, 1500, 2000 mm

SPARE HOSE FOR INFLATING GUN  
WITH ZAMA HEAD (ART.53DZ) OR  
BRASS HEAD (ART.53DOT)  
Length hose: 300, 500, 750, 1000,  
1500, 2000 mm

## ART. 56ZM



TESTINA GONFIAGGIO  
IN ZAMA  
• Ø 6

ZAMA INFLATING HEAD  
• Ø 6

## ART. 56OT



TESTINA GONFIAGGIO  
IN OTTONE

- Ø 6
- Ø 7
- Ø 8

BRASS INFLATING HEAD  
• Ø 6  
• Ø 7  
• Ø 8

## ART. 56OTF



TESTINA GONFIAGGIO  
IN OTTONE  
Filetto: • 1/8 F

BRASS INFLATING HEAD  
Thread: • 1/8 F

## ART. 56RI



GUARNIZIONE RICAMBIO  
TESTINA GONFIAGGIO  
A- ZAMA  
B- OTTONE

SPARE GASKET HEAD  
INFLATION  
A- ZAMA  
B- BRASS

## ART. 3000R



GUARNIZIONE RICAMBIO  
PER SERBATOIO  
PER ART. 2900 - MASTER 2900  
MASTER 3000  
PROFI MASTER 3000

SPARE GASKET FOR TANK  
FOR ART. 2900 - MASTER 2900  
MASTER 3000  
PROFI MASTER 3000

## ART. 57R



GUARNIZIONE RICAMBIO  
PER SERBATOIO  
PER ART. 57 - 58 - 62 - 62A  
62SV - 65 - 65SV  
MASTER 2800  
PROFI MASTER 2800

SPARE GASKET FOR TANK  
FOR ART. 57 - 58 - 62 - 62A  
62SV - 65 - 65SV  
MASTER 2800  
PROFI MASTER 2800

## ART. 152



KIT TESTINE PER  
PALLONE, CICLO E CANOTTO

*INFLATING HEAD KIT FOR  
BALLS, CYCLE AND FOR RUBBER  
BOAT*

## ART. 151



TESTINA PER PROVA  
PRESSIONE PER ART. 54  
• Ø6

*HEAD FOR PRESSURE TEST  
FOR ART. 54*  
• Ø6

## ART. 53F



TUBO DI RICAMBIO PER  
ART. 152-154-155-156-157  
Lunghezza tubo: 130 mm

*SPARE HOSE FOR  
ART. 152-154-155-156-157  
Lenght hose: 130 mm*

## ART. 156



TESTINA GONFIAGGIO  
PER CICLO

*INFLATING HEAD  
CYCLE*

## ART. 155



TESTINA GONFIAGGIO  
PER PALLONE

*INFLATING HEAD  
FOR BALLS*

## ART. 157



TESTINA GONFIAGGIO  
PER CANOTTO

*INFLATING HEAD  
FOR RUBBER BOATS*

## ART. 154



TESTINA GONFIAGGIO  
PER CICLO DA CORSA

*INFLATING HEAD  
FOR RACING CYCLE*

## ART. 158



GUARNIZIONE RICAMBIO  
PER ART. 154 - 156

*SPARE GASKET  
FOR ART. 154 - 156*

## ART. 53B



MANOMETRO PER PISTOLA  
GONFIAGGIO ATTACCO  
RADIALE 1/4  
0-12 bar • Ø 63  
0-175 psi

*GAUGE FOR INFLATING GUN  
RADIAL CONNECTION 1/4  
0-12 bar • Ø 63  
0-175 psi*

## ART. 53BP



MANOMETRO PER PISTOLA  
GONFIAGGIO ATTACCO  
POSTERIORE 1/4  
0-12 bar • Ø 63  
0-175 psi • Ø 80

*GAUGE FOR INFLATING GUN  
BACK CONNECTION 1/4  
0-12 bar • Ø 63  
0-175 psi • Ø 80*

## ART. 73RD



MANOMETRO OMOLOGATO CE  
DOPPIA SCALA PER PISTOLA  
GONFIAGGIO ATTACCO  
RADIALE 1/4  
0-10 bar • Ø 63  
0-145 psi

*GAUGE APPROVED EC DOUBLE  
SCALE FOR INFLATING GUN  
RADIAL CONNECTION 1/4  
0-10 bar • Ø 63  
0-145 psi*

## ART. 63R



MANOMETRO OMOLOGATO  
CE PER PISTOLA GONFIAGGIO  
ATTACCO POSTERIORE 1/4  
0-10 bar • Ø 63

*GAUGE APPROVED EC  
FOR INFLATING GUN  
BACK CONNECTION 1/4  
0-10 bar • Ø 63*

## ART. 73R



MANOMETRO OMOLOGATO CE  
PER PISTOLA GONFIAGGIO  
ATTACCO RADIALE 1/4  
0-10 bar • Ø 63

*GAUGE APPROVED EC  
FOR INFLATING GUN  
RADIAL CONNECTION 1/4  
0-10 bar • Ø 63*

## ART. 83R



MANOMETRO OMOLOGATO CE  
DOPPIA SCALA PER PISTOLA  
GONFIAGGIO  
ATTACCO POSTERIORE 1/4  
0-10 bar • Ø 80  
0-145 psi

*GAUGE APPROVED EC DOUBLE  
SCALE FOR INFLATING GUN  
BACK CONNECTION 1/4  
0-10 bar • Ø 80  
0-145 psi*

## ART. 53BDG



MANOMETRO DIGITALE PER  
PISTOLA GONFIAGGIO ATTACCO  
RADIALE 1/4 COMPLETO  
DI PROTEZIONE BLU  
0-12 bar • Ø 63  
0-175 psi

*DIGITAL GAUGE FOR INFLATING  
GUN RADIAL CONNECTION 1/4  
BLUE PROTECTION INCLUSIVE  
0-12 bar • Ø 63  
0-175 psi*

## ART. 54R



MANOMETRO PER PROVA  
PRESSIONE ATTACCO RADIALE  
CON RESCA Ø 7  
0-12 bar • Ø 63  
0-175 psi

*GAUGE FOR PRESSURE GAUGE  
RADIAL CONNECTION  
WITH FITTING Ø 7  
0-12 bar • Ø 63  
0-175 psi*

## ART. 53C



PROTEZIONE PER MANOMETRO  
ATTACCO RADIALE  
• Ø 63

*PROTECTION FOR GAUGE  
RADIAL CONNECTION  
• Ø 63*

## ART. 53C2



PROTEZIONE PER MANOMETRO  
ATTACCO POSTERIORE  
• Ø 63  
• Ø 80

*PROTECTION FOR GAUGE  
BACK CONNECTION  
• Ø 63  
• Ø 80*



## ART. 153



FILTRO PER PISTOLA  
DI VERNICIATURA CON  
SERBATOIO INFERIORE

*FILTER FOR SPRAY GUN  
LOWER TANK*

## ART. 153A



FILTRO PER PISTOLA  
DI VERNICIATURA CON  
SERBATOIO SUPERIORE

*FILTER FOR SPRAY GUN  
UPPER TANK*

## ART. 55SR



SERBATOIO DI RICAMBIO  
ACCIAIO VERNICIATO KG 1  
PER ART. 55 - 92B

*TANK SPARE PART  
PAINTED STEEL KG 1  
FOR ART. 55 - 92B*

## ART. 57SR



SERBATOIO DI RICAMBIO  
IN ALLUMINIO CHIUSURA A  
BAIONETTA KG 1  
PER ART. 57 - 58 - 66 - 65 - 62  
62A - MASTER 2800 - PROFI  
MASTER 2800

*ALUMINIUM TANK SPARE PART  
BAYONET LOCK KG 1  
FOR ART. 57 - 58 - 66 - 65 - 62  
62A - MASTER 2800 - PROFI  
MASTER 2800*

## ART. 61SR



SERBATOIO SUPERIORE  
DI RICAMBIO  
IN ALLUMINIO KG 0,5  
PER ART. 61 - 61SV  
Filetto 1/4 gas

*ALUMINUM TOP TANK  
SPARE PART KG 0,5  
FOR ART. 61 - 61SV  
Thread 1/4 gas*

## ART. 61ASR



SERBATOIO SUPERIORE DI  
RICAMBIO  
IN ALLUMINIO KG 1  
PER ART. 61 - 61SV  
Filetto 1/4 gas

*ALUMINUM TOP TANK  
SPARE PART KG 1  
FOR ART. 61 - 61SV  
Thread 1/4 gas*

## ART. 61BSR



SERBATOIO SUPERIORE  
DI RICAMBIO  
IN NYLON KG 0,5  
PER ART. 61A - MASTER 3100 -  
PROFI MASTER 3100  
Filetto 1/4 gas

*ALUMINUM TOP TANK  
SPARE PART KG 0,5  
FOR ART. 61A - MASTER 3100 -  
PROFI MASTER 3100  
Thread 1/4 gas*


## ART. 3000SA



SERBATOIO DI RICAMBIO  
IN ALLUMINIO CHIUSURA  
AUTOCLAVE KG 1  
PER ART. 2900 - MASTER 2900  
MASTER 3000  
PROFI MASTER 3000

*ALUMINIUM TANK  
SPARE PART FOR CLOSURE  
WITH CLAMP TYPE KG 1  
FOR ART. 2900 - MASTER 2900  
MASTER 3000  
PROFI MASTER 3000*


**RICAMBI PER PISTOLA DI GONFIAGGIO ART. 53**  
**SPARE PARTS FOR INFLATING GUN ART. 53**



- 1 - TUBO COMPLETO
- 2 - COPRIMANOMETRO
- 3 - MANOMETRO
- 4 - VALVOLA SFIATO
- 5 - IMPUGNATURA
- 6 - INNESTO TIPO ?
- 26 - NYPLESS
- 27 - GHIERA

- 1 - HOSE COMPLETE
- 2 - GAUGE PROTECTION
- 3 - GAUGE
- 4 - RELIEF VALVE
- 5 - HANDLE
- 6 - PLUG TYPE ?
- 26 - NYPLESS
- 27 - MILLED NUT

**RICAMBI PER PISTOLA DI LAVAGGIO CON SERBATOIO IN ACCIAIO ART. 55**  
**SPARE PARTS FOR WASHING GUN WITH STEEL CUP ART. 55**




- 1 - SERBATOIO kg 1
- 2 - BECCUCCIO E DADO BLOCCAGGIO
- 3 - CANNA INTERNA - ESTERNA
- 4 - IMPUGNATURA
- 5 - INNESTO TIPO ?
- 26 - NYPLESS
- 27 - GHIERA

- 1 - TANK kg 1
- 2 - NOZZLE AND NUT
- 3 - INSIDE - OUTSIDE PIPE
- 4 - HANDLE
- 5 - PLUG TYPE ?
- 26 - NYPLESS
- 27 - MILLED NUT


## RICAMBI PER PISTOLA DI VERNICIATURA ART. 61E ART. 62 SPARE PARTS FOR SPRAY GUN ART. 61AND ART. 62

- 1 - VOLANTINO REGOLAZIONE VENTAGLIO
- 2 - DADO PREMISTOPPA CON GUARNIZIONE
- 3 - SERBATOIO SUPERIORE  
CAPACITÀ 0,5 - 1 kg
- 4 - GHIERA
- 5 - TESTA DIREZIONE VENTAGLIO
- 6 - DUSE POLVERIZ. (UGELLO)  
Ø 1-1,2-1,5-1,8-2-2,5-3
- 7 - PREMISTOPPA
- 9 - VITE PREMISTOPPA
- 10 - COPERCHIO
- 11 - DADO BLOCCAGGIO COPERCHIO
- 12 - GUARNIZIONE
- 13 - TUBO PESCANTE
- 14 - SERBATOIO CAPACITÀ 0,5 - 1 kg
- 16 - MOLLA PER AGO
- 17 - VOLANTINO REGOLAZIONE AGO
- 18 - TAPPO VALVOLA ARIA
- 19 - MOLLA VALVOLA ARIA
- 20 - VALVOLA ARIA CON O.R.
- 21 - ASTINA DI APERTURA VALVOLA
- 22 - LEVA DI COMANDO
- 23 - PERNO LEVA DI COMANDO
- 24 - MANICO
- 26 - NYPLESS
- 27 - GHIERA
- 30 - TAPPO



- 1 - JET DISTRIBUTOR CONTROL KNOB
- 2 - GLAND NUT WITH SEAL
- 3 - 1,1 - 2,2 lb UPPER TANK
- 4 - METAL RING
- 5 - JET DISTRIBUTOR HEAD DIRECTION
- 6 - DUSE PULVERIZING (NOZZLE)  
Ø 1-1,2-1,5-1,8-2-2,5-3
- 7 - GLAND
- 9 - GLAND SCREW
- 10 - COVER
- 11 - COVER BLOCKING NUT
- 12 - GASKET
- 13 - INTEKE PIPE
- 14 - 1,1 - 2,2 lb LOWER TANK
- 16 - NEEDLE SPRING
- 17 - NEEDLE CONTROL KNOB
- 18 - AIR VALVE CAP
- 19 - SPRING AIR VALVE
- 20 - AIR VALVE WITH O.R.
- 21 - OPENING VALVE ROD
- 22 - LEVER
- 23 - PIVOT LEVER
- 24 - HANDLE
- 26 - NYPLESS
- 27 - METAL RING
- 30 - PLUG

## RICAMBI PER PISTOLA DI SOFFIAGGIO ART. 50 SPARE PARTS FOR BLOW GUN ART. 50



- 1 - BECCUCCIO
- 2 - IMPUGNATURA
- 3 - INNESTO TIPO ?
- 26 - NYPLESS
- 27 - GHIERA

- 1 - NOZZLE
- 2 - HANDLE
- 3 - PLUG TYPE ?
- 26 - NYPLESS
- 27 - MILLED NUT

**SU RICHIESTA I NOSTRI PRODOTTI POSSONO ESSERE FORNITI IN BLISTER  
ON REQUEST, OUR PRODUCTS CAN BE SUPPLIED IN BLISTER**



## RIDUTTORI DI PRESSIONE • PRESSURE REDUCER

PORTATA ARIA / AIR FLOW : 1800 l/min.  
 PRESSIONE MAX / MAX PRESSURE : 12 bar

### ART. 620R



RIDUTTORE DI PRESSIONE  
 CON MANOMETRO E  
 RUBINETTO DI LINEA

Filetto: • 3/8  
 • 1/2

*PRESSURE REDUCER VALVE  
 WITH GAUGE AND LINE VALVES*

Thread: • 3/8  
 • 1/2

PORTATA ARIA / AIR FLOW : 1700 l/min.  
 PRESSIONE MAX / MAX PRESSURE : 12 bar

### ART. 600R



RIDUTTORE DI PRESSIONE 1/4

• 3 fori  
 • 4 fori

*PRESSURE REDUCER 1/4*

• 3 holes  
 • 4 holes

### ART. 610R



RIDUTTORE DI PRESSIONE  
 CON MANOMETRO E  
 RUBINETTO CORSOIO

Filetto: • 3/8  
 • 1/2

*PRESSURE REDUCER  
 WITH GAUGE AND  
 SLIDING TAP*

Thread: • 3/8  
 • 1/2

### ART. 605R 1/4



RIDUTTORE DI PRESSIONE  
 CON MANOMETRO Ø 40  
 E RUBINETTO CORSOIO

*PRESSURE REDUCER  
 WITH GAUGE Ø 40  
 AND SLIDING TAP*

### ART. 630R



RIDUTTORE DI PRESSIONE  
 CON MANOMETRO E RUBINETTO  
 RAPIDO UNIVERSALE

Filetto: • 3/8  
 • 1/2

*PRESSURE REDUCER  
 WITH GAUGE AND UNIVERSAL  
 SNAP COUPLING*

Thread: • 3/8  
 • 1/2

### ART. 601R 1/4



RIDUTTORE DI PRESSIONE  
 CON MANOMETRO Ø 40  
 E RUBINETTO DI LINEA

*PRESSURE REDUCER  
 WITH GAUGE Ø 40  
 AND LINE VALVE*

### ART. 603



SQUADRA FISSAGGIO A  
 PARETE  
 PER ART. 600R - 601R - 602R - 605R

*WALL BRACKET  
 FOR ART. 600R - 601R - 602R - 605R*

### ART. 602R 1/4



RIDUTTORE DI PRESSIONE  
 CON MANOMETRO Ø 40  
 E RUBINETTO RAPIDO  
 UNIVERSALE

*PRESSURE REDUCER  
 WITH GAUGE Ø 40 AND  
 UNIVERSAL SNAP COUPLING*

### ART. 606



MANOMETRO PER  
 RIDUTTORE 0-12 BAR

Filetto: • 1/8 - Ø 40  
 • 1/8 - Ø 50

*GAUGE FOR REDUCER  
 0-12 BAR*

Thread: • 1/8 - Ø 40  
 • 1/8 - Ø 50

### ART. 604



DADO BLOCCAGGIO  
 PASSAPARETE  
 PER ART. 600R - 601R - 602R - 605R

*LOCKNUT  
 FOR ART. 600R - 601R - 602R - 605R*

**GRUPPI MODULARI FILTRO/REGOLATORE/LUBRIFICATORE PER ARIA COMPRESSA**  
**MODULAR GROUPS: FILTER/REGULATOR/LUBRICATOR FOR COMPRESSED AIR**

**PRESSIONE MASSIMA DI INGRESSO 18 bar • MAXIMUM INLET PRESSURE 18 bar**



FILTRO SEPARATORE DI CONDENSA  
TAZZA IN METALLO

*STEAM SEPARATOR FILTER  
METAL CUP*

**ART. 720FM 1/4**

**ART. 725FM 3/8**

**ART. 730FM 1/2**

**ART. 735FM 3/4**

**ART. 740FM 1"**

GRADO DI FILTRAZIONE 20 µm  
DEGREE OF FILTRATION 20 µm



REGOLATORE DI PRESSIONE CON MANOMETRO  
*PRESSURE REGULATOR WITH GAUGE*

**ART. 721R 1/4**

**ART. 726R 3/8**

**ART. 731R 1/2**

**ART. 736R 3/4**

**ART. 741R 1"**



LUBRIFICATORE A MICRONEBBIA  
TAZZA IN METALLO

*OIL-MIST LUBRICATOR  
METAL CUP*

**ART. 722LM 1/4**

**ART. 727LM 3/8**

**ART. 732LM 1/2**

**ART. 737LM 3/4**

**ART. 742LM 1"**



FILTRO REGOLATORE DI PRESSIONE  
CON MANOMETRO, TAZZA IN METALLO

*FILTER - REGULATOR WITH GAUGE  
METAL CUP*

ART. **723FRM 1/4**

ART. **728FRM 3/8**

ART. **733FRM 1/2**

ART. **738FRM 3/4**

ART. **743FRM 1"**

GRADO DI FILTRAZIONE 20 µm  
DEGREE OF FILTRATION 20 µm



GRUPPO COMPLETO A DUE ELEMENTI:  
FILTRO REGOLATORE + LUBRIFICATORE  
CON MANOMETRO, TAZZE IN METALLO

*COMPLETE GROUP TWO ELEMENTS:  
FILTER REGULATOR + LUBRICATOR  
WITH GAUGE, METAL CUP*

ART. **724FR+LM 1/4**

ART. **729FR+LM 3/8**

ART. **734FR+LM 1/2**

ART. **739FR+LM 3/4**

ART. **744FR+LM 1"**

GRADO DI FILTRAZIONE 20 µm  
DEGREE OF FILTRATION 20 µm



GRUPPO COMPLETO A TRE ELEMENTI:  
FILTRO + REGOLATORE +  
LUBRIFICATORE CON MANOMETRO  
TAZZE IN METALLO

*COMPLETE GROUP THREE ELEMENTS:  
FILTER + REGULATOR + LUBRICATOR  
WITH GAUGE, METAL CUP*

ART. **745F+R+LM 1/4**

ART. **746F+R+LM 3/8**


ART. **747F+R+LM 1/2**

ART. **748F+R+LM 3/4**

ART. **749F+R+LM 1"**

GRADO DI FILTRAZIONE 20 µm  
DEGREE OF FILTRATION 20 µm

## ART. 19



ATTACCO BAIONETTA  
FILETTO MASCHIO

*BAYONET JOINT  
WITH MALE THREAD*


FILETTO / THREAD

1/8

1/4

3/8

## ART. 20



ATTACCO BAIONETTA  
FILETTO FEMMINA

*BAYONET JOINT  
WITH FEMALE THREAD*

FILETTO / THREAD

1/8

1/4

3/8

## ART. 20A



ATTACCO BAIONETTA PER TUBO  
GOMMA E POLIURETANO

*BAYONET JOINT FOR RUBBER  
AND POLYURETHANE HOSE*

Ø	Ø	Ø
6x10	7x16	8x17
6x12	8x12	10x15
6x13	8x13	10x17
6x14	8x15	10x19

## ART. 21A



ATTACCO BAIONETTA  
PORTAGOMMA CON RESCA

*BAYONET JOINT  
FOR RUBBER HOSE*

Ø	Ø
6	10
7	11
8	12
9	14

## ART. 22A




RACCORDO CON DADO  
FRESATO FILETTO MASCHIO  
TENUTA CON OR

*JOINT WITH MILLED NUT  
MALE THREAD WITH OR*

FILETTO / THREAD

1/4

## ART. 22



RACCORDO CON DADO  
FRESATO FILETTO MASCHIO

*JOINT WITH MILLED NUT  
MALE THREAD*

FILETTO / THREAD

1/8

1/4

3/8

1/2

## ART. 22B



RACCORDO CON DADO  
FRESATO FILETTO FEMMINA

*JOINT WITH MILLED NUT  
FEMALE THREAD*

FILETTO / THREAD

1/8

1/4

3/8

## ART. 22D



RACCORDO DI GIUNZIONE  
CON DADI FRESATI

*JOINT OF JUCTION  
WITH MILLED NUTS*

FILETTO / THREAD

1/4 x 1/4

## ART. 22E



RACCORDO GIUNZIONE  
A "T" CON DADI FRESATI

*"T" JOINT WITH MILLED NUTS*

FILETTO / THREAD

1/4

## ART. 22C



RACCORDO GIUNZIONE A  
CROCE, CON DADI FRESATI  
E FILETTO MASCHIO CONICO

*CROSS JOINT WITH MILLED  
NUTS AND MALE CONICAL THREAD*

FILETTO / THREAD

1/4

3/8



## ART. 22F



DADO FRESATO

MILLED NUT

FILETTO / THREAD

1/4
14/125
3/8

## ART. 20R



GOMMINO RICAMBIO  
PER ATTACCO A BAIONETTA

SPARE GASKET FOR  
BAYONET JOINT

## ART. 21



RACCORDO CON FILETTO MASCHIO  
CILINDRICO PORTAGOMMA

JOINT WITH CYLINDRICAL MALE  
THREAD FOR RUBBER HOSE

FILETTO / THREAD      Ø

FILETTO / THREAD	Ø	FILETTO / THREAD	Ø
1/8	6 - 7 - 8 - 9 - 10	1/2	8 - 10 - 11 - 12 - 14 16 - 17 - 18 - 19 20 - 21 - 22
1/4	6 - 7 - 8 - 9 - 10 11 - 12 - 14	3/4	16 - 17 - 18 - 20 - 25
3/8	6 - 8 - 9 - 10 - 11 12 - 14 - 16 - 17	1"	25 - 30

## ART. 21F



RACCORDO CON FILETTO FEMMINA  
CILINDRICO PORTAGOMMA

JOINT WITH CYLINDRICAL FEMALE  
THREAD FOR RUBBER HOSE

FILETTO / THREAD	Ø	FILETTO / THREAD	Ø
1/8	6 - 7 - 8 - 9 - 10	3/8	6 - 8 - 9 - 10 - 11 12 - 14 - 16 - 17 - 19
1/4	6 - 7 - 8 - 9 10 - 11 - 12	1/2	8 - 10 - 12 - 14 - 16 17 - 18 - 20 - 21 - 22

## ART. 160



DOPPIA RESCA

DOUBLE CONNECTION

Ø	Ø	Ø
6	9	12
7	10	13
8	11	14

## ART. 27C



RACCORDO CON RESCA GIREVOLE  
FILETTO FEMMINA

REVOLVING JOINT WITH FEMALE  
THREAD FOR RUBBER HOSE

FILETTO / THREAD	Ø
1/4	6 - 7 - 7,4 - 8
3/8	8 - 9 - 10 - 11

## ART. 20D




RACCORDO CON FILETTO MASCHIO  
CILINDRICO PER TUBO GOMMA E  
POLIURETANO

JOINT WITH CYLINDRICAL MALE  
THREAD FOR RUBBER AND  
POLYURETHANE HOSE

FILETTO / THREAD	Ø	FILETTO / THREAD	Ø
1/4 3/8	6x10 - 6x12 6x13 - 6x14 - 7x16 8x12 - 8x13 - 8x15 8x17 - 10x15 10x17 - 10x19	3/8	11x16

## ART. 20C



RACCORDO CON FILETTO  
FEMMINA PER TUBO GOMMA E  
POLIURETANO

JOINT WITH FEMALE THREAD FOR  
RUBBER AND POLYURETHANE HOSE

FILETTO / THREAD	Ø
1/4 3/8	6x10 - 6x12 - 6x13 6x14 - 7x16 - 8x12 8x13 - 8x15 - 8x17 10x15 - 10x17 - 10x19

## ART. 25HP



RACCORDO FILETTO FEMMINA  
CON DADO GIREVOLE  
PER TUBO SPIRALE

JOINT WITH FEMALE THREAD  
AND REVOLVING NUT  
FOR SPIRAL HOSE

FILETTO / THREAD	Ø
1/4	6x8

## ART. 20HP



RACCORDO FILETTO FEMMINA  
CON DADO GIREVOLE  
PER TUBO GOMMA

JOINT WITH FEMALE THREAD  
AND REVOLVING NUT  
FOR RUBBER HOSE

FILETTO / THREAD	Ø
1/4	6x10 - 6x12 6x13 - 6x14

## ART. 25F

RACCORDO FILETTO MASCHIO  
CILINDRICO PER TUBO SPIRALE E  
POLIURETANO

*JOINT WITH CYLINDRICAL MALE  
THREAD FOR SPIRAL AND  
POLYURETHANE HOSE*



FILETTO / THREAD	Ø
1/4	4x6 - 5x8 - 6x8
	6,5x10 - 8x10
	8x12 - 10x12
3/8	6x8 - 6,5x10
	8x10 - 8x12
	10x12

## ART. 25M

RACCORDO FILETTO FEMMINA  
PER TUBO SPIRALE E POLIURETANO

*JOINT WITH FEMALE THREAD FOR  
SPIRAL AND POLYURETHANE HOSE*



FILETTO / THREAD	Ø
1/4	4x6 - 5x8 - 6x8
	6,5x10 - 8x10
	8x12 - 10x12
3/8	6,5x10 - 8x10
	8x12 - 10x12

## ART. 25G

RACCORDO ATTACCO  
BAIONETTA PER TUBO SPIRALE

*BAYONET JOINT  
FOR SPIRAL HOSE*



Ø
4x6
6x8
8x10
10x12

## ART. 25I

RACCORDO ATTACCO  
BAIONETTA PER TUBO SPIRALE

*BAYONET REVOLVING JOINT  
FOR SPIRAL HOSE*



Ø
4x6
5x8
6x8
6,5x10
8x10
8x12
10x12

## ART. 25H

RACCORDO GIREVOLE CON  
FILETTO MASCHIO CILINDRICO PER  
TUBO SPIRALE E POLIURETANO

*REVOLVING JOINT WITH  
CYLINDRICAL MALE THREAD FOR  
SPIRAL AND POLYURETHANE HOSE*




FILETTO / THREAD	Ø
1/4	4x6 - 5x8 - 6x8
	6,5x10 - 8x10
	8x12 - 10x12
3/8	5x8 - 6x8
	6,5x10 - 8x10
	8x12 - 10x12

## ART. 25HF

RACCORDO GIREVOLE CON  
FILETTO FEMMINA PER TUBO  
SPIRALE E POLIURETANO

*REVOLVING JOINT WITH FEMALE  
THREAD FOR SPIRAL AND  
POLYURETHANE HOSE*




FILETTO / THREAD	Ø
1/4	4x6 - 5x8 - 6x8
	6,5x10 - 8x10
	8x12 - 10x12
3/8	5x8 - 6x8
	6,5x10 - 8x10
	8x12 - 10x12

## ART. 25HS

RACCORDO GIREVOLE FILETTO  
MASCHIO-MASCHIO CILINDRICO

*REVOLVING JOINT WITH  
CYLINDRICAL MALE-MALE THREAD*



FILETTO / THREAD
1/4
3/8
1/2

## ART. 25HT

RACCORDO GIREVOLE FILETTO  
FEMMINA-MASCHIO CILINDRICO

*REVOLVING JOINT WITH  
CYLINDRICAL FEMALE-MALE  
THREAD*



FILETTO / THREAD
1/4
3/8
1/2

## ART. 25HC

RACCORDO GIREVOLE CON FILETTO MASCHIO CILINDRICO PER TUBO SPIRALE E POLIURETANO TENUTA CON OR




*REVOLVING JOINT WITH MALE THREAD FOR SPIRAL AND POLYURETHANE HOSE SEAL WITH OR*

FILETTO / THREAD	Ø	FILETTO / THREAD	Ø
1/4	4x6	1/4	8x10
	5x8		8x12
	6x8		10x12
	6,5x10		

## ART. 25HN

RACCORDO GIREVOLE CON FILETTO MASCHIO CILINDRICO PER TUBO GOMMA E POLIURETANO TENUTA CON OR




*REVOLVING JOINT WITH MALE CYLINDRICAL THREAD FOR RUBBER AND POLYURETHANE HOSE SEAL WITH OR*

FILETTO / THREAD	Ø	FILETTO / THREAD	Ø
1/4	6x10	1/4	8x12
	6x12		8x13
	6x13		8x15
	6x14		8x17

## ART. 20CG

RACCORDO GIREVOLE CON FILETTO FEMMINA PER TUBO GOMMA E POLIURETANO




*REVOLVING JOINT WITH FEMALE THREAD FOR RUBBER AND POLYURETHANE HOSE*

FILETTO / THREAD	Ø	FILETTO / THREAD	Ø
1/4	6x10	1/4	8x12
	6x12		8x13
	6x13		8x15
	6x14		8x17

## ART. 20DG

RACCORDO GIREVOLE CON FILETTO MASCHIO CILINDRICO PER TUBO GOMMA E POLIURETANO




*REVOLVING JOINT WITH MALE CYLINDRICAL THREAD FOR RUBBER AND POLYURETHANE HOSE*

FILETTO / THREAD	Ø	FILETTO / THREAD	Ø
1/4	6x10	1/4	8x12
	6x12		8x13
	6x13		8x15
	6x14		8x17

## ART. 25HG

RACCORDO GIREVOLE CON FILETTO FEMMINA PER TUBO GOMMA E POLIURETANO



*REVOLVING JOINT WITH FEMALE THREAD FOR RUBBER AND POLYURETHANE HOSE*

FILETTO / THREAD	Ø
1/4	6
	7
	8
	10

## ART. 25HM

RACCORDO GIREVOLE CON FILETTO FEMMINA PER TUBO NYLON E POLIURETANO



*REVOLVING JOINT WITH FEMALE THREAD FOR NYLON AND POLYURETHANE HOSE*

FILETTO / THREAD	Ø
1/4	4x6
	5x8
	6x8
	6,5x10
	8x10

## ART. 25HE

RACCORDO GIREVOLE CON FILETTO MASCHIO CILINDRICO PER TUBO GOMMA E POLIURETANO




*REVOLVING JOINT WITH MALE CYLINDRICAL THREAD FOR RUBBER AND POLYURETHANE HOSE*

FILETTO / THREAD	Ø	FILETTO / THREAD	Ø
1/4	6	3/8	8
	7		9
	8		10
	10		12

## ART. 25HR

RACCORDO GIREVOLE CON FILETTO MASCHIO CILINDRICO PER TUBO GOMMA E POLIURETANO TENUTA CON OR



*REVOLVING JOINT WITH MALE CYLINDRICAL THREAD FOR RUBBER AND POLYURETHANE HOSE SEAL WITH OR*

FILETTO / THREAD	Ø
1/4	6
	7
	8
	10

## ART. 25HD

RACCORDO GIREVOLE CON FILETTO MASCHIO CILINDRICO PER TUBO NYLON E POLIURETANO TENUTA CON OR

REVOLVING JOINT WITH MALE CYLINDRICAL THREAD FOR NYLON AND POLYURETHANE HOSE SEAL WITH OR



FILETTO / THREAD	Ø
1/4	4x6
	5x8
	6x8
	6,5x10
	8x10

## ART. 25HL

RACCORDO GIREVOLE CON FILETTO MASCHIO CILINDRICO PER TUBO NYLON E POLIURETANO


REVOLVING JOINT WITH MALE CYLINDRICAL THREAD FOR NYLON AND POLYURETHANE HOSE



FILETTO / THREAD	Ø
1/4	4x6
	5x8
	6x8
	6,5x10
	8x10

## ART. 58NCO

NIPPO CONICO ORIENTABILE  
CONICAL ORIENTABLE NIPPLE



FILETTO / THREAD
1/8
1/4
3/8
1/2
3/4
1"

## ART. 58TPL

RACCORDO PASSAPARETE FEMMINA PASSANTE

FEMALE JOINT BULKHEAD



FILETTO/THREAD	MAX SPESSORE/MAX THICKNESS	FORO PARETE/WALL HOLE
1/8	10	16x1,5
1/4	15	20x1,5
3/8	15	26x1,5
1/2	20	28x1,5

## ART. 28

BOCCHETTONE PER TUBO RAME  
UNION FOR COPPER HOSE




FILETTO / THREAD	Ø
3/8	8 - 10 - 12
1/2	12 - 14 - 16
3/4	16 - 18 - 20

## ART. 28A

NIPPO CILINDRICO PER FISSAGGIO TUBO RAME

CYLINDRICAL NIPPLE FOR FIXING COPPER HOSE




FILETTO / THREAD	Ø
3/8	8 - 10 - 12
1/2	12 - 14 - 16
3/4	16 - 18 - 20

## ART. 28B

"L" PER FISSAGGIO TUBO RAME

"L" FOR FIXING COPPER HOSE



FILETTO / THREAD	A x B
	3/8 x 3/8
	1/2 x 3/8
	1/2 x 1/2

**ART. 29**VALVOLA A SFERA  
FILETTO FEMMINA-FEMMINA*BALL VALVE FEMALE-FEMALE  
THREAD*

FILETTO / THREAD

1/8

1/4

3/8

1/2

3/4

**ART. 29A**VALVOLA A SFERA  
FILETTO MASCHIO-FEMMINA*BALL VALVE MALE-FEMALE  
THREAD*

FILETTO / THREAD

1/8

1/4

3/8

1/2

3/4

**ART. 30**RUBINETTO LINEA CON  
CHIAVETTA FILETTO MASCHIO*LINE COCK MALE THREAD*

FILETTO / THREAD

1/8

1/4

3/8

1/2

**ART. 30A**RUBINETTO LINEA CON  
VOLANTINO FILETTO MASCHIO*LINE COCK MALE THREAD  
WITH HANDWHEEL*


FILETTO / THREAD

1/8

1/4

3/8

1/2

**ART. 30Z**RUBINETTO LINEA CON CHIAVETTA  
FILETTO MASCHIO CONICO  
IN ZAMA NICHELATO*NICKELED ZAMA LINE COCK  
CONICAL MALE THREAD*

FILETTO / THREAD

1/4

**ART. 30B**RUBINETTO LINEA FILETTO  
FEMMINA-FEMMINA*LINE VALVE  
FEMALE-FEMALE THREAD*

FILETTO / THREAD

1/8x1/8

1/4x1/4

**ART. 75**RUBINETTO A CORSOIO  
ENTRATA FILETTO MASCHIO*SLIDE COCK WITH MALE THREAD AND  
MILLED NUT*

FILETTO / THREAD

1/8

1/4

3/8

1/2

**ART. 75B**RUBINETTO A CORSOIO  
ENTRATA PORTAGOMMA*SLIDE COCK WITH BAYONET  
JOINT FOR RUBBER HOSE*

Ø

6x12

6x14

8x17

10x19

**ART. 75D**RUBINETTO A CORSOIO  
ENTRATA TUBO A SPIRALE*SLIDE COCK WITH BAYONET  
JOINT FOR SPIRAL HOSE*

Ø

4x6

6x8

8x10

10x12

**ART. 27B**

CONTRO DADO

NUT



FILETTO / THREAD

10x1

1/8

1/4

3/8

1/2

## ART. 58T



TAPPO IN OTTONE NICHELATO FILETTO MASCHIO CILINDRICO

*NICKELLED BRASS CYLINDRICAL PLUG WITH MALE THREAD*

FILETTO / THREAD

1/8
1/4
3/8
1/2
3/4
1"

## ART. 58TF



TAPPO IN OTTONE NICHELATO FILETTO FEMMINA

*NICKELLED BRASS PLUG WITH FEMALE THREAD*

FILETTO / THREAD

1/8
1/4
3/8
1/2
3/4
1"

## ART. 58TG



TAPPO IN OTTONE NICHELATO FILETTO MASCHIO CILINDRICO TENUTA CON OR CHIAVE ESAGONALE INTERNA

*NICKELLED BRASS PLUG WITH CYLINDRICAL MALE THREAD AND KEEPING WITH OR INTERNAL HEXAGONAL WRENCH*

FILETTO / THREAD

1/8	1/2
1/4	3/4
3/8	1"

## ART. 58TC



TAPPO IN OTTONE NICHELATO FILETTO MASCHIO CONICO CON CHIAVE ESAGONALE INTERNA

*NICKELLED BRASS CONICAL PLUG WITH MALE THREAD AND INTERNAL HEXAGON WRENCH*

FILETTO / THREAD

1/8
1/4
3/8
1/2
3/4
1"

## ART. 58RR



RIDUZIONE IN OTTONE NICHELATO CILINDRICA A SCOMPARSA PASSANTE

*NICKELLED BRASS CYLINDRICAL HIDDEN REDUCER*

FILETTO / THREAD

1/4x1/8
3/8x1/4
1/2x3/8
3/4x1/2
1"x3/4

## ART. 58TM




TAPPO IN OTTONE NICHELATO A SCOMPARSA CILINDRICO

*NICKELLED BRASS CYLINDRICAL HIDDEN PLUG*

FILETTO / THREAD

1/8
1/4
3/8
1/2
3/4

## ART. 58N




NIPPO IN OTTONE NICHELATO FILETTO CILINDRICO PARALLELI E RIDOTTI

*NICKELLED BRASS NIPPLE WITH CYLINDRICAL THREAD PARALLEL AND REDUCER*

FILETTO / THREAD

1/8x1/8	1/8x1/4	3/8x1/2
1/4x1/4	1/8x3/8	3/8x3/4
3/8x3/8	1/8x1/2	1/2x3/4
1/2x1/2	1/4x3/8	1/2x1"
3/4x3/4	1/4x1/2	3/4x1"
1"x1"		

## ART. 58NC



NIPPO IN OTTONE NICHELATO FILETTO CONICO PARALLELI E RIDOTTI

*NICKELLED BRASS NIPPLE WITH CONICAL THREAD PARALLEL AND REDUCER*

FILETTO / THREAD

1/8x1/8	1/8x1/4	3/8x1/2
1/4x1/4	1/8x3/8	3/8x3/4
3/8x3/8	1/8x1/2	1/2x3/4
1/2x1/2	1/4x3/8	1/2x1"
3/4x3/4	1/4x1/2	3/4x1"
1"x1"		

## ART. 58R




RIDUZIONE IN OTTONE NICHELATO FILETTO MASCHIO CILINDRICO PARALLELI E RIDOTTI

*NICKELLED BRASS REDUCER WITH CYLINDRICAL THREAD PARALLEL AND REDUCER*

FILETTO / THREAD (MxF)

1/8x1/8	1/8x1/4	3/8x1/2
1/4x1/4	1/8x3/8	3/8x3/4
3/8x3/8	1/8x1/2	1/2x3/4
1/2x1/2	1/4x3/8	1/2x1"
3/4x3/4	1/4x1/2	3/4x1"
1"x1"		

## ART. 58FMC



RIDUZIONE IN OTTONE NICHELATO FILETTO MASCHIO CONICO PARALLELI E RIDOTTI

*NICKELLED BRASS REDUCER WITH CONICAL THREAD PARALLEL AND REDUCER*

FILETTO / THREAD (MxF)

1/8x1/8	1/4x1/2	3/4x3/4
1/8x1/4	3/8x3/8	3/4x1"
1/8x3/8	3/8x1/2	1"x1"
1/4x1/4	1/2x1/2	
1/4x3/8	1/2x3/4	

## ART. 58RC

RIDUZIONE IN OTTONE NICHELATO  
FILETTO MASCHIO CONICO

*NICKELED BRASS REDUCER WITH MALE CONICAL THREAD*



FILETTO / THREAD (MxF)	
1/4x1/8	3/4x1/4
3/8x1/8	3/4x3/8
3/8x1/4	3/4x1/2
1/2x1/8	1"x1/2
1/2x1/4	1"x3/4
1/2x3/8	

## ART. 58RFC

RIDUZIONE IN OTTONE NICHELATO  
FILETTO MASCHIO CILINDRICO

*NICKELED BRASS REDUCER WITH MALE CYLINDRICAL THREAD*




FILETTO / THREAD (MxF)	
1/4x1/8	3/4x1/4
3/8x1/8	3/4x3/8
3/8x1/4	3/4x1/2
1/2x1/8	1"x1/2
1/2x1/4	1"x3/4
1/2x3/8	

## ART. 58RP

PROLUNGA IN OTTONE NICHELATO  
MASCHIO-FEMMINA

*NICKELED BRASS MALE-FEMALE PROLONGED REDUCER*



FILETTO / THREAD	H
1/8x1/8	36
1/8x1/8	45
1/4x1/4	27
1/4x1/4	43

## ART. 58M

MANICOTTO IN OTTONE NICHELATO  
FILETTO FEMMINA PASSANTE E RIDOTTI

*NICKELED BRASS SLEEVE WITH CYLINDRICAL FEMALE THREAD PARALLEL AND REDUCER*




FILETTO / THREAD (MxF)		
1/8x1/8	1/4x1/2	1/2x1"
1/8x1/4	3/8x3/8	3/4x3/4
1/8x3/8	3/8x1/2	3/4x1"
1/8x1/2	3/8x3/4	1"x1"
1/4x1/4	1/2x1/2	
1/4x3/8	1/2x3/4	

## ART. 26

RUBINETTO SCARICO CONDENSA  
FILETTO MASCHIO TENUTA CON OR

*CONDENSATE DRAIN COCK MALE THREAD SEAL WITH OR*



FILETTO / THREAD
1/8
1/4
3/8
1/2

## ART. 26A

RUBINETTO SCARICO CONDENSA  
FILETTO MASCHIO TENUTA CON OR

*CONDENSATE DRAIN COCK MALE THREAD SEAL WITH OR*



FILETTO / THREAD
1/8
1/4
3/8
1/2

## ART. 26B

RUBINETTO SCARICO CONDENSA  
FILETTO MASCHIO TENUTA MECCANICA

*CONDENSATE DRAIN COCK MALE THREAD MECHANICAL SEAL*



FILETTO / THREAD
1/8
1/4
3/8
1/2

## ART. 26C

RONDELLE IN ALLUMINIO

*ALUMINIUM WASHER*



Ø
1/8
1/4
3/8
1/2
3/4
1"

## ART. 1A



RACCORDO STAMPATO A "L"  
IN OTTONE NICHELATO  
MASCHIO-MASCHIO CONICO

"L" JOINT MALE-MALE CONICAL  
NICKELED BRASS

FILETTO / THREAD

1/8
1/4
3/8
1/2
3/4
1"

## ART. 2A



RACCORDO STAMPATO A "L"  
IN OTTONE NICHELATO  
MASCHIO CONICO - FEMMINA

"L" JOINT MALE CONICAL - FEMALE  
NICKELED BRASS

FILETTO / THREAD

1/8
1/4
3/8
1/2
3/4
1"

## ART. 3A



RACCORDO STAMPATO A "L"  
IN OTTONE NICHELATO  
FEMMINA-FEMMINA

"L" JOINT FEMALE-FEMALE  
NICKELED BRASS

FILETTO / THREAD

1/8
1/4
3/8
1/2
3/4
1"

## ART. 1T



RACCORDO STAMPATO A "T"  
IN OTTONE NICHELATO  
2 FEMMINE - 1 MASCHIO CONICO

"T" JOINT 2 FEMALE - 1 MALE CONICAL  
NICKELED BRASS

FILETTO / THREAD

1/8
1/4
3/8
1/2
3/4
1"

## ART. 2T




RACCORDO STAMPATO A "T"  
IN OTTONE NICHELATO  
1 MASCHIO CONICO - 2 FEMMINE

"T" JOINT 1 MALE CONICAL - 2 FEMALE  
NICKELED BRASS

FILETTO / THREAD

1/8
1/4
3/8
1/2
3/4
1"

## ART. 3T



RACCORDO STAMPATO A "T"  
IN OTTONE NICHELATO  
3 FEMMINE

"T" JOINT 3 FEMALE  
NICKELED BRASS

FILETTO / THREAD

1/8
1/4
3/8
1/2
3/4
1"

## ART. 5T



RACCORDO STAMPATO A "T"  
IN OTTONE NICHELATO  
2 MASCHI CONICI - 1 FEMMINA

"T" JOINT 2 MALE CONICAL - 1 FEMALE  
NICKELED BRASS

FILETTO / THREAD

1/8
1/4
3/8
1/2
3/4
1"

## ART. 4T



RACCORDO STAMPATO A "T"  
IN OTTONE NICHELATO  
2 MASCHI CONICI - 1 FEMMINA

"T" JOINT 2 MALE CONICAL - 1 FEMALE  
NICKELED BRASS

FILETTO / THREAD

1/8
1/4
3/8
1/2
3/4
1"

## ART. 1C



RACCORDO STAMPATO A "+"  
IN OTTONE NICHELATO  
3 FEMMINE - 1 MASCHIO CONICO

"+" JOINT 3 FEMALE - 1 MALE CONICAL  
NICKELED BRASS

FILETTO / THREAD

1/8
1/4
3/8
1/2

## ART. 2C



RACCORDO STAMPATO A "+"  
IN OTTONE NICHELATO  
4 FEMMINE

"+" JOINT 4 FEMALE NICKELED BRASS

FILETTO / THREAD

1/8
1/4
3/8
1/2



## ART. 27

DEVIAZIONE STAMPATA A "Y"  
IN OTTONE NICHELATO  
1 MASCHIO - 2 FEMMINE

"Y" JOINT 1 MALE - 2 FEMALE  
NICKELLED BRASS



FILETTO / THREAD

1/8
1/4
3/8
1/2

## ART. 27A

DEVIAZIONE STAMPATA A "Y"  
IN OTTONE NICHELATO  
3 FEMMINE

"Y" JOINT 3 FEMALE  
NICKELLED BRASS




FILETTO / THREAD

1/8
1/4
3/8
1/2

## ART. 27D

RACCORDO STAMPATO A "L"  
IN OTTONE NICHELATO  
PORTAGOMMA MASCHIO CONICO

"L" JOINT FOR RUBBER HOSE  
WITH MALE CONICAL THREAD




FILETTO / THREAD	Ø
1/8	6
	7
	8
1/4	6
	7
	8
	9
	10

## ART. 27E

RACCORDO STAMPATO A "L"  
IN OTTONE NICHELATO  
MASCHIO CONICO - FEMMINA  
RIDOTTO

"L" JOINT REDUCED  
MALE CONICAL - FEMALE THREAD  
NICKELLED BRASS



FILETTO / THREAD	A	B
	3/8	1/4
3/8	1/2	
1/2	1/4	
1/2	3/8	

Assemblaggio pistole  
Assembly of guns

## ART. 500



RACCORDO DIRITTO IN OTTONE NICHELATO FILETTO MASCHIO CONICO

STRAIGHT MALE CONICAL JOINT NICKELLED BRASS

FILETTO / THREAD	TUBO/HOSE	FILETTO / THREAD	TUBO/HOSE
1/8	4x6 - 6x8 8x10	3/8	4x6 - 6x8 8x10 - 10x12
1/4	4x6 - 6x8 8x10 - 10x12	1/2	8x10 - 10x12 12,5x15

## ART. 501



RACCORDO DIRITTO IN OTTONE NICHELATO FILETTO FEMMINA

STRAIGHT JOINT FEMALE THREAD NICKELLED BRASS

FILETTO / THREAD	TUBO / HOSE	FILETTO / THREAD	TUBO / HOSE
1/8	4x6 - 6x8 8x10	1/4	4x6 - 6x8 8x10
		3/8	6x8 - 8x10 10x12

## ART. 502



RACCORDO INTERMEDIO IN OTTONE NICHELATO

STRAIGHT CONNECTOR NICKELLED BRASS

TUBO/HOSE
4x6
6x8
8x10
10x12
12,5x15

## ART. 503



RACCORDO STAMPATO A "T" IN OTTONE NICHELATO FILETTO MASCHIO CENTRALE CONICO

"T" JOINT CENTRE MALE CONICAL THREAD NICKELLED BRASS

FILETTO / THREAD	TUBO / HOSE
1/8	4x6 - 6x8
1/4	4x6 - 6x8 - 8x10

## ART. 509



DADO PER RACCORDO A CALZAMENTO IN OTTONE NICHELATO

NUT FOR PUSH-IN FITTINGS NICKELLED BRASS

FILETTO / THREAD	TUBO/HOSE
10x1	4x6
12x1	6x8
14x1	8x10
16x1	10x12
20x1	12,5x15

## ART. 504



RACCORDO STAMPATO A "L" IN OTTONE NICHELATO FILETTO FEMMINA

"L" JOINT FEMALE THREAD NICKELLED BRASS

FILETTO / THREAD	TUBO/HOSE
1/8	4x6 6x8
1/4	6x8 8x10

## ART. 505



RACCORDO STAMPATO A "L" IN OTTONE NICHELATO FILETTO MASCHIO CONICO

"L" JOINT MALE CONICAL THREAD NICKELLED BRASS

FILETTO / THREAD	TUBO / HOSE	FILETTO / THREAD	TUBO / HOSE
1/8	4x6 - 6x8	3/8	6x8 - 8x10 10x12
1/4	4x6 - 6x8 8x10 - 10x12	1/2	12,5x15

## ART. 506



RACCORDO STAMPATO A "T" INTERMEDIO IN OTTONE NICHELATO

INTERMEDIATE "T" CONNECTOR NICKELLED BRASS

TUBO/HOSE
4x6
6x8
8x10

## ART. 508



RACCORDO STAMPATO A "T" IN OTTONE NICHELATO FILETTO MASCHIO LATERALE CONICO

"T" JOINT SIDE MALE CONICAL THREAD NICKELLED BRASS

FILETTO / THREAD	TUBO / HOSE
1/8	4x6 - 6x8
1/4	4x6 - 6x8 - 8x10

**ART. 520**



**RACCORDO DIRITTO MASCHIO CONICO TEFLONATO IN OTTONE NICHELATO**

*CONICAL MALE STRAIGHT JOINT NICKELED BRASS*

FILETTO / THREAD	Ø	FILETTO / THREAD	Ø
1/8	4 - 6 - 8	3/8	8 - 10 - 12 - 14
1/4	4 - 6 - 8 - 10 - 12	1/2	10 - 12 - 14

**ART. 521**




**RACCORDO A "L" GIREVOLE MASCHIO CONICO TEFLONATO IN OTTONE NICHELATO**

*CONICAL MALE REVOLVING "L" JOINT NICKELED BRASS*

FILETTO / THREAD	Ø	FILETTO / THREAD	Ø
1/8	4 - 6 - 8	3/8	8 - 10 - 12 - 14
1/4	4 - 6 - 8 - 10 - 12	1/2	10 - 12 - 14

**ART. 522**




**RACCORDO A "T" LATERALE GIREVOLE MASCHIO CONICO TEFLONATO IN OTTONE NICHELATO**

*CONICAL LATERAL MALE REVOLVING "T" JOINT NICKELED BRASS*

FILETTO / THREAD	Ø
1/8	4 - 6 - 8
1/4	6 - 8 - 10
3/8	8 - 10 - 12

**ART. 523**



**RACCORDO A "T" IN OTTONE NICHELATO AL CENTRO GIREVOLE CONICO TEFLONATO**

*CONICAL CENTRE MALE REVOLVING "T" JOINT NICKELED BRASS*

FILETTO / THREAD	Ø
1/8	4 - 6 - 8
1/4	6 - 8 - 10
3/8	8 - 10 - 12

**ART. 524**




**RACCORDO DIRITTO INTERMEDIO IN OTTONE NICHELATO**

*STRAIGHT INTERMEDIATE JOINT NICKELED BRASS*

Ø
4
6
8
10
12
14

**ART. 525**



**RACCORDO A "L" INTERMEDIO IN OTTONE NICHELATO**

*"L" INTERMEDIATE JOINT NICKELED BRASS*

Ø
4
6
8
10
12
14

**ART. 526**



**RACCORDO A "T" INTERMEDIO IN OTTONE NICHELATO**

*"T" INTERMEDIATE JOINT NICKELED BRASS*

Ø
4
6
8
10
12
14

**ART. 527**



**RACCORDO DIRITTO INTERMEDIO RIDOTTO IN OTTONE NICHELATO**

*STRAIGHT INTERMEDIATE REDUCER NICKELED BRASS*

Ø A	Ø B
4	6
6	8
8	10

**ART. 528**



**PROLUNGA GIUNZIONE**

*STRAIGHT PLUG-IN*

Ø
4
6
8
10
12
14

**ART. 529**



**TAPPO MASCHIO**

*MALE PLUG-IN*

Ø
4
6
8
10
12
14

**ART. 530**

RACCORDO DIRITTO MASCHIO CILINDRICO FILETTO GAS E METRICO

CYLINDRICAL MALE STRAIGHT JOINT GAS AND METRIC THREAD

FILETTO / THREAD	Ø
1/4	4 - 6 - 8 - 10 - 12
3/8	8 - 10 - 12 - 14
1/2	8 - 10 - 12 - 14



FILETTO / THREAD	Ø
M5	4
1/8	4 - 6 - 8 - 10

**ART. 531**

RACCORDO DIRITTO TONDO CILINDRICO FILETTO METRICO

CYLINDRICAL MALE STRAIGHT ROUND JOINT METRIC THREAD

FILETTO / THREAD	Ø
M5	4 - 6
M6	4



**ART. 532**

RACCORDO DIRITTO FEMMINA CILINDRICO FILETTO GAS E METRICO

CYLINDRICAL FEMALE STRAIGHT JOINT GAS AND METRIC THREAD

FILETTO / THREAD	Ø
M5	4
1/8	4 - 6 - 8
1/4	4 - 6 - 8



**ART. 533**

RACCORDO A "T" MASCHIO CILINDRICO AL CENTRO GIREVOLE FILETTO GAS E METRICO

CYLINDRICAL MALE REVOLVING CENTRE "T" JOINT GAS AND METRIC THREAD

FILETTO / THREAD	Ø
1/4	6 - 8 - 10 - 12
3/8	8 - 10 - 12
1/2	10 - 12



FILETTO / THREAD	Ø
M5	4 - 6
1/8	4 - 6 - 8

**ART. 534**

RACCORDO A "L" MASCHIO CILINDRICO GIREVOLE FILETTO GAS E METRICO

CYLINDRICAL MALE REVOLVING "L" JOINT GAS AND METRIC THREAD

FILETTO / THREAD	Ø
1/4	4 - 6 - 8 - 10 - 12
3/8	8 - 10 - 12 - 14
1/2	10 - 12 - 14



FILETTO / THREAD	Ø
M5	4 - 6
1/8	4 - 6 - 8

**ART. 535**

RACCORDO A "T" MASCHIO CILINDRICO LATERALE GIREVOLE FILETTO GAS E METRICO

CYLINDRICAL MALE REVOLVING LATERAL "T" JOINT GAS AND METRIC THREAD

FILETTO / THREAD	Ø
1/4	6 - 8 - 10
3/8	8 - 10 - 12



FILETTO / THREAD	Ø
M5	4
1/8	4 - 6 - 8

**ART. 536**

RACCORDO PASSAPARETE UNION BULKHEAD JOINT

Ø	FILETTO / THREAD
4	M11
6	M14
8	M16
10	M18
12	M22
14	M24



**ART. 537**

RACCORDO FEMMINA PASSAPARETE STRAIGHT FEMALE BULKHEAD JOINT

FILETTO / THREAD	Ø
1/4	6 - 8 - 10 - 12
3/8	8 - 10 - 12 - 14
1/2	12



FILETTO / THREAD	Ø
M5	4 - 6
1/8	4 - 6 - 8

**ART. 538**

RACCORDO A "Y" INNESTABILE "Y" JOINT

Ø A	Ø B
6	6
8	8
10	8
10	10



**ART. 539**

RACCORDO ADATTATORE RIDUZIONE - MAGGIORAZIONE REDUCER-INCREASER PLUG-IN

Ø A	Ø B	Ø A	Ø B
4	6 - 8	8	6 - 10 - 12 - 14
6	4 - 8 - 10 - 12	10	12 - 14



## ART. 800



RACCORDO DIRITTO  
MASCHIO CILINDRICO  
FILETTO GAS E METRICO

CYLINDRICAL MALE STRAIGHT  
JOINT GAS AND METRIC THREAD

FILETTO / THREAD	Ø	FILETTO / THREAD	Ø
M5	4 - 6	1/4	4 - 6 - 8 10 - 12
M6	4 - 6	3/8	6 - 8 - 10 12 - 14 - 16
1/8	4 - 6 - 8 - 10	1/2	8 - 10 - 12 14 - 15 - 16

## ART. 801



RACCORDO A "L"  
MASCHIO CILINDRICO GIREVOLE  
FILETTO GAS E METRICO

CYLINDRICAL MALE REVOLVING "L"  
JOINT GAS AND METRIC THREAD

FILETTO / THREAD	Ø	FILETTO / THREAD	Ø
M5	4 - 6	1/4	4 - 6 - 8 10 - 12
M6	4 - 6	3/8	4 - 6 - 8 10 - 12 - 14
1/8	4 - 6 - 8 - 10	1/2	8 - 10 - 12 14 - 15 - 16

## ART. 802



RACCORDO DIRITTO  
FEMMINA FILETTO GAS E METRICO

FEMALE STRAIGHT JOINT  
GAS AND METRIC THREAD

FILETTO / THREAD	Ø	FILETTO / THREAD	Ø
M5	6	1/4	6 - 8 - 10
1/8	4 - 6 - 8	3/8	8 - 10
		1/2	10 - 12

## ART. 803



RACCORDO A "L"  
FEMMINA CILINDRICO GIREVOLE  
FILETTO GAS E METRICO

CYLINDRICAL FEMALE REVOLVING  
"L" JOINT GAS AND METRIC THREAD

FILETTO / THREAD	Ø	FILETTO / THREAD	Ø
1/8	4 - 6 - 8	1/4	6 - 8
		3/8	10
		1/2	12

## ART. 804



RACCORDO A "T" MASCHIO  
CILINDRICO AL CENTRO GIREVOLE  
FILETTO GAS E METRICO

CYLINDRICAL MALE  
REVOLVING CENTRE "T" JOINT  
GAS AND METRIC THREAD

FILETTO / THREAD	Ø	FILETTO / THREAD	Ø
M5	4 - 6	1/4	6 - 8 - 10 - 12
1/8	4 - 6 - 8	3/8	10 - 12

## ART. 805



RACCORDO A "L"  
MASCHIO CILINDRICO  
GIREVOLE LUNGO  
FILETTO GAS E METRICO

CYLINDRICAL MALE REVOLVING  
LONG "L" JOINT  
GAS AND METRIC THREAD

FILETTO / THREAD	Ø
1/8	6 - 8
1/4	6 - 8
3/8	10 - 12

## ART. 806




RACCORDO A "T" MASCHIO  
CILINDRICO LATERALE GIREVOLE  
FILETTO GAS E METRICO

CYLINDRICAL MALE REVOLVING  
LATERAL "T" JOINT  
GAS AND METRIC THREAD

FILETTO / THREAD	Ø	FILETTO / THREAD	Ø
1/8	4 - 6 - 8	1/4	6 - 8 - 10
		3/8	10
		1/2	12

## ART. 807



RACCORDO A "T" INTERMEDIO

"T" INTERMEDIATE JOINT

Ø A	Ø B
4	4
6	4 - 6
8	4 - 6 - 8
10	6 - 8 - 10
12	8 - 10 - 12
14	14
15	15
16	16

## ART. 808



DIRITTO INTERMEDIO  
STRAIGHT INTERMEDIATE JOINT

Ø A	Ø B
4	4
6	4 - 6
8	4 - 6 - 8
10	6 - 8 - 10
12	8 - 10 - 12
14	14
15	15
16	16

## ART. 809



RACCORDO A "L" INTERMEDIO  
"L" INTERMEDIATE JOINT

Ø
4
6
8
10
12
14
15
16

## ART. 810

RACCORDO A "Y" INNESTABILE

"Y" JOINT



Ø A	Ø B
4	4
6	4 - 6
8	6 - 8
10	8 - 10
12	10 - 12

## ART. 811

RACCORDO A "Y" MASCHIO CILINDRICO GIREVOLE

CYLINDRICAL MALE REVOLVING "Y" JOINT



FILETTO / THREAD	Ø
1/8	4 - 6 - 8
1/4	6 - 8 - 10
3/8	10 - 12

## ART. 812

RACCORDO A "Y" PARI CON CODOLO

"Y" JOINT WITH PLUG-IN




Ø
4
6
8
10
12

## ART. 813

RACCORDO A "+" INTERMEDIO

INTERMEDIATE "+" JOINT



Ø
4
6
8
10
12

## ART. 814

RACCORDO A "L" INTERMEDIO CON CODOLO

"L" JOINT INTERMEDIATE WITH PLUG-IN



Ø
4
6
8
10
12

## ART. 815

RACCORDO ADATTATORE RIDUZIONE - MAGGIORAZIONE

REDUCER-INCREASER PLUG-IN



Ø A	Ø B
6	4
8	4 - 6
10	6 - 8
12	8 - 10

## ART. 816

RACCORDO PASSAPARETE

UNION BULKHEAD JOINT



Ø	M
4	M12x1
6	M14x1
8	M16x1
10	M20x1
12	M22x1

## ART. 817

RACCORDO A "L" PASSAPARETE

UNION BULKHEAD "L" JOINT



Ø	M
4	M12x1
6	M14x1
8	M16x1
10	M20x1

## ART. 818

RACCORDO PASSAPARETE FEMMINA

FEMALE UNION BULKHEAD JOINT



FILETTO / THREAD	Ø
1/8	4 - 6
1/4	6 - 8
3/8	10
1/2	12

## ART. 819

TAPPO MASCHIO

MALE PLUG-IN



Ø
4
6
8
10
12

## ART. 99

RACCORDO CON OGIVA DIRITTO  
MASCHIO CONICO  
IN OTTONE NICHELATO

CONICAL MALE STRAIGHT  
JOINT WITH OGIVE  
NICKELLED BRASS



FILETTO / THREAD	Ø
1/8	4 - 6 - 8
1/4	6 - 8 - 10
3/8	8 - 10 - 12
1/2	10 - 12 - 14 15 - 16 - 18

## ART. 100

RACCORDO CON OGIVA DIRITTO  
MASCHIO CILINDRICO  
IN OTTONE NICHELATO

CYLINDRICAL MALE STRAIGHT  
JOINT WITH OGIVE  
NICKELLED BRASS



FILETTO / THREAD	Ø
1/8	4 - 6 - 8
1/4	6 - 8 - 10
3/8	8 - 10
1/2	10 - 14

## ART. 101

RACCORDO CON OGIVA A "L"  
MASCHIO CONICO  
IN OTTONE NICHELATO

CONICAL MALE "L"  
JOINT WITH OGIVE  
NICKELLED BRASS



FILETTO / THREAD	Ø
1/8	4 - 6 - 8
1/4	6 - 8 - 10
3/8	8 - 10 - 12 - 14
1/2	10 - 12 - 14 15 - 16 - 18

## ART. 102

RACCORDO CON OGIVA DIRITTO  
FEMMINA CILINDRICO  
IN OTTONE NICHELATO

CYLINDRICAL FEMALE STRAIGHT  
JOINT WITH OGIVE  
NICKELLED BRASS



FILETTO / THREAD	Ø
1/8	4 - 6 - 8
1/4	6 - 8 - 10
3/8	8 - 10 - 12
1/2	12 - 14 15 - 16 - 18

## ART. 103

RACCORDO CON OGIVA A "L"  
FEMMINA CILINDRICO  
IN OTTONE NICHELATO

CYLINDRICAL FEMALE "L"  
JOINT WITH OGIVE  
NICKELLED BRASS



FILETTO / THREAD	Ø
1/8	4 - 6 - 8
1/4	6 - 8

## ART. 104

RACCORDO CON OGIVA A "L"  
INTERMEDIO  
IN OTTONE NICHELATO

"L" INTERMEDIATE  
JOINT WITH OGIVE  
NICKELLED BRASS



Ø
4
6
8
10
12
14
15
16
18

## ART. 105

RACCORDO CON OGIVA A "T"  
MASCHIO CONICO AL CENTRO  
IN OTTONE NICHELATO

CONICAL CENTRE MALE "T"  
JOINT WITH OGIVE  
NICKELLED BRASS



FILETTO / THREAD	Ø
1/8	4 - 6 - 8
1/4	6 - 8 - 10
3/8	8 - 10 - 12
1/2	12 - 14 15 - 16 - 18

## ART. 106

RACCORDO CON OGIVA A "T"  
MASCHIO CONICO LATERALE  
IN OTTONE NICHELATO

CONICAL LATERAL MALE "T"  
JOINT WITH OGIVE  
NICKELLED BRASS



FILETTO / THREAD	Ø
1/8	4 - 6 - 8
1/4	6 - 8 - 10
3/8	8 - 10 - 12
1/2	12 - 14 15 - 16 - 18

## ART. 107



RACCORDO CON OGIVA A "T"  
INTERMEDIO  
IN OTTONE NICHELATO

"T" INTERMEDIATE JOINT WITH  
OGIVE NICKELED BRASS

Ø
4
6
8
10
12
14
15
16
18

## ART. 108




RACCORDO CON OGIVA DIRITTO  
INTERMEDIO  
IN OTTONE NICHELATO

STRAIGHT INTERMEDIATE JOINT  
WITH OGIVE NICKELED BRASS

Ø
4
6
8
10
12
14
15
16
18

## ART. 108A



RACCORDO CON OGIVA  
PASSAPARETE  
IN OTTONE NICHELATO

UNION BULKHEAD JOINT  
WITH OGIVE NICKELED BRASS

Ø	A Max
6	15,5
8	16,5
10	15,5
12	16
14	18
15	18

## ART. 108B



OGIVA IN OTTONE

BRASS OGIVE

Ø
4
6
8
10
12
14
15
16
18

## ART. 108C



DADO IN OTTONE NICHELATO

NICKELED BRASS NUT

FILETTO / THREAD	Ø
M8x1	4
M10x1	6
M12x1	8
M16x1,5	10
M18x1,5	12
M22x1,5	14
M22x1,5	15
M24x1,5	16
M26x1,5	18

## ART. 108D




BOCCOLA DI SUPPORTO IN OTTONE

BRASS SUPPORT BUCKLE

Ø
2
2,5
4
6
8
9
10
12
12,5
14
15



PORTATA ARIA / AIR FLOW: 2500 l/min  
 PRESSIONE ARIA / MAX PRESSURE: 12 bar  
 TEMPERATURA / TEMPERATURE: -18 °C ÷ +80 °C



**ART. 37**

RUBINETTO RAPIDO GIGANTE  
ATTACCO FILETTO MASCHIO

GIANT QUICK BALL COUPLER  
WITH MALE THREAD



FILETTO / THREAD
3/8
1/2

**ART. 39**

INNESTO GIGANTE  
ATTACCO FILETTO MASCHIO

GIANT CONNECTION WITH  
MALE THREAD



FILETTO / THREAD
3/8
1/2

**ART. 36**

RUBINETTO RAPIDO GIGANTE  
ATTACCO FILETTO FEMMINA

GIANT QUICK BALL COUPLER  
WITH FEMALE THREAD



FILETTO / THREAD
3/8
1/2

**ART. 40**

INNESTO GIGANTE  
ATTACCO PORTAGOMMA

GIANT CONNECTION FOR RUBBER  
HOSE



Ø TUBO / HOSE	Ø TUBO / HOSE
10x19	13x19
10x20	13x20
10x21	13x21
10x22	13x23
10x23	13x24
	13x25

**ART. 38**

RUBINETTO RAPIDO GIGANTE  
ATTACCO PORTAGOMMA

GIANT QUICK BALL COUPLER  
FOR RUBBER HOSE



Ø TUBO / HOSE	Ø TUBO / HOSE
10x19	13x19
10x20	13x20
10x21	13x21
10x22	13x23
10x23	13x24
	13x25

**ART. 35A**

RACCORDO A BAIONETTA GIGANTE  
ATTACCO PORTAGOMMA

GIANT BAYONET CONNECTION  
FOR RUBBER HOSE



Ø TUBO / HOSE	Ø TUBO / HOSE
10x19	13x19
10x20	13x20
10x21	13x21
10x22	13x23
10x23	13x24
	13x25

**ART. 35B**

RACCORDO GIGANTE  
ATTACCO PORTAGOMMA  
FILETTO MASCHIO

GIANT JOINT FOR RUBBER HOSE  
WITH MALE THREAD



FILETTO/THREAD	Ø TUBO/HOSE	FILETTO/THREAD	Ø TUBO/HOSE
3/8 1/2	10x19	3/8 1/2	13x19
	10x20		13x20
	10x21		13x21
	10x22		13x23
	10x23		13x24
	10x23		13x25

**ART. 35BG**

RACCORDO GIGANTE GIREVOLE  
ATTACCO PORTAGOMMA  
FILETTO MASCHIO

GIANT REVOLVING JOINT  
MALE THREAD FOR RUBBER HOSE



FILETTO/THREAD	Ø TUBO/HOSE	FILETTO/THREAD	Ø TUBO/HOSE
1/2	10x19	1/2	13x19
	10x20		13x20
	10x21		13x21
	10x22		13x23
	10x23		13x24
	10x23		13x25

**ART. 35**



RACCORDO CON DADO GIGANTE  
ATTACCO FILETTO MASCHIO

JOINT WITH GIANT NUT  
MALE THREAD

FILETTO / THREAD

3/8

1/2

**ART. 35G**



RACCORDO GIUNZIONE CON 2  
DADI GIGANTI

JOINT WITH 2 GIANT NUT

FILETTO / THREAD

1/2

**ART. 35D**



DADO FARFALLA GIGANTE

GIANT NUT

FILETTO / THREAD

1/2

**ART. 35GR**




GUARNIZIONE RICAMBIO  
PER Art. 35A

SPARE GASKET  
FOR ART. 35A



MOTO GUZZI FALCONE SPORT 500 cc.

PORTATA ARIA / AIR FLOW: 1100 l/min  
 PRESSIONE ARIA / MAX PRESSURE: 12 bar  
 TEMPERATURA / TEMPERATURE: -18 °C ÷ +80 °C



**ART. 117**

RUBINETTO RAPIDO "MIGNON"  
 A SFERA  
 ATTACCO FILETTO MASCHIO

"MIGNON" QUICK BALL COUPLER  
 WITH MALE THREAD



FILETTO / THREAD

1/8

1/4

**ART. 112**

INNESTO "MIGNON"  
 ATTACCO FILETTO MASCHIO

"MIGNON" CONNECTION  
 WITH MALE THREAD



FILETTO / THREAD

1/8

1/4

**ART. 118**

RUBINETTO RAPIDO "MIGNON"  
 A SFERA  
 ATTACCO FILETTO FEMMINA

"MIGNON" QUICK BALL COUPLER  
 WITH FEMALE THREAD



FILETTO / THREAD

1/8

1/4

**ART. 113**

INNESTO "MIGNON"  
 ATTACCO FILETTO FEMMINA

"MIGNON" CONNECTION  
 WITH FEMALE THREAD



FILETTO / THREAD

1/8

1/4

**ART. 111**

RUBINETTO RAPIDO "MIGNON"  
 A SFERA PER TUBO SPIRALE

"MIGNON" QUICK BALL COUPLER  
 FOR SPIRAL HOSE



∅

4x6

6x8

8x10

**ART. 115**

INNESTO "MIGNON"  
 ATTACCO TUBO SPIRALE

"MIGNON" CONNECTION  
 FOR SPIRAL HOSE



∅

4x6

6x8

8x10

**ART. 110**

RUBINETTO RAPIDO "MIGNON"  
 A SFERA PER TUBO SPIRALE

"MIGNON" QUICK BALL COUPLER  
 FOR SPIRAL HOSE



∅

4x6

6x8

8x10

**ART. 116**

INNESTO "MIGNON"  
 ATTACCO TUBO SPIRALE

"MIGNON" CONNECTION  
 FOR SPIRAL HOSE



∅

4x6

6x8

8x10

**ART. 119**

RUBINETTO RAPIDO "MIGNON"  
 A SFERA ATTACCO PORTAGOMMA  
 "MIGNON" QUICK BALL COUPLER  
 FOR RUBBOR HOSE



∅

6

8

**ART. 114**

INNESTO "MIGNON"  
 ATTACCO PORTAGOMMA

"MIGNON" CONNECTION  
 FOR RUBBER HOSE



∅

6

8

## ART. 109



RUBINETTO RAPIDO "MIGNON"  
PASSAPARETE

"MIGNON" QUICK BALL COUPLER  
TO UNION BULKHEAD

FILETTO / THREAD	Ø
4 x 6	
6 x 8	

## ART. 109A



RUBINETTO RAPIDO "MIGNON"  
"SCANIA" CON VALVOLA  
FILETTO FEMMINA

"MIGNON" "SCANIA"  
QUICK BALL COUPLER WITH VALVE  
FEMALE THREAD

FILETTO / THREAD	Ø
8V1-2	

## ART. 109B



RUBINETTO RAPIDO "MIGNON"  
FILETTO FEMMINA "STRALIS"

"MIGNON" "STRALIS" QUICK BALL  
COUPLER WITH FEMALE THREAD

FILETTO / THREAD	Ø
16 x 1,5	

## ART. 117B



RACCORDO GIREVOLE "STRALIS"  
"STRALIS" REVOLVING JOINT

FILETTO / THREAD	Ø
16 x 1,5	4x6 6x8

## ART. 117C



RACCORDO CON VALVOLA "SCANIA"  
FILETTO FEMMINA

"SCANIA" JOINT WITH VALVE  
FEMALE THREAD

FILETTO / THREAD	Ø
1/8 x 8V1-2	

## ART. 117F



RACCORDO "STRALIS" FEMMINA  
IN OTTONE NICHELATO

"STRALIS" JOINT WITH  
FEMALE THREAD NICKELED BRASS

FILETTO / THREAD	Ø
1/8 x 16 x 1,5	
1/4 x 16 x 1,5	

## ART. 117E



RACCORDO PASSAPARETE  
UNION BULKHEAD JOINT

FILETTO / THREAD	Ø
1/8	4 x 6
1/8	6 x 8

## ART. 117M




RACCORDO "STRALIS" MASCHIO  
IN OTTONE NICHELATO

MALE STRALIS JOINT  
NICKELED BRASS

FILETTO / THREAD	Ø
1/4 x 16 x 1,5	

## ART. 117D




KIT RUBINETTO RAPIDO MIGNON  
A SFERA COMPONENTI TIPO:  
STRALIS, SCANIA (CON VALVOLA),  
E PASSAPARETE

KIT QUICK COUPLER UNIT TYPE:  
STRALIS, SCANIA (WITH VALVE),  
AND UNION BULKHEAD

FILETTO / THREAD	Ø
4x6	
6x8	

PORTATA ARIA / AIR FLOW: 1600 l/min  
 PRESSIONE ARIA / MAX PRESSURE: 12 bar  
 TEMPERATURA / TEMPERATURE: -18 °C ÷ +80 °C



RUBINETTI RAPIDI SERIE ITALIA - QUICK TAPS AND FITTINGS ITALY SERIES

## ART. 45

RUBINETTO RAPIDO A SFERA  
 ATTACCO FILETTO MASCHIO

QUICK BALL COUPLER  
 WITH MALE THREAD



FILETTO / THREAD
1/8
1/4
3/8
1/2

## ART. 23B

INNESTO ATTACCO  
 FILETTO MASCHIO

CONNECTION MALE THREAD



FILETTO / THREAD	
1/8	3/8
1/4	1/2

DISPONIBILI ANCHE IN VERSIONE TEMPERATA  
 AVAILABLE ALSO IN TEMPERED VERSION

## ART. 47

RUBINETTO RAPIDO A SFERA  
 ATTACCO FILETTO FEMMINA

QUICK BALL COUPLER  
 WITH FEMALE THREAD




FILETTO / THREAD
1/8
1/4
3/8
1/2

## ART. 23C

INNESTO ATTACCO  
 FILETTO FEMMINA

CONNECTION FEMALE THREAD



FILETTO / THREAD	
1/8	
1/4	
3/8	
1/2	

DISPONIBILI ANCHE IN VERSIONE TEMPERATA  
 AVAILABLE ALSO IN TEMPERED VERSION

## ART. 46

RUBINETTO RAPIDO A SFERA  
 ATTACCO PORTAGOMMA

QUICK BALL COUPLER  
 FOR RUBBER HOSE



Ø	Ø	Ø
6x10	7x16	8x17
6x12	8x12	10x15
6x13	8x13	10x17
6x14	8x15	10x19

## ART. 23

INNESTO ATTACCO  
 PORTAGOMMA

CONNECTION FOR  
 RUBBER HOSE



Ø	Ø	Ø
6x10	7x16	8x17
6x12	8x12	10x15
6x13	8x13	10x17
6x14	8x15	10x19

## ART. 48

RUBINETTO RAPIDO A SFERA  
 ATTACCO TUBO SPIRALE

QUICK BALL COUPLER  
 FOR SPIRAL HOSE



Ø	Ø
4x6	8x10
5x8	8x12
6x8	10x12
6,5x10	

## ART. 25E

INNESTO ATTACCO  
 PORTAGOMMA

CONNECTION  
 FOR SPIRAL HOSE



Ø	Ø
4x6	8x10
5x8	8x12
6x8	10x12
6,5x10	

## ART. 44

RUBINETTO RAPIDO A SFERA  
 ATTACCO PORTAGOMMA

QUICK BALL COUPLER  
 FOR RUBBER HOSE



Ø	Ø	Ø
6	9	12
7	10	13
8	11	14

## ART. 23E

INNESTO ATTACCO PORTAGOMMA  
 CONNECTION FOR RUBBER HOSE



Ø	Ø
6	10
7	11
7,4	12
8	13
9	14

**ART. 23I**

INNESTO RAPIDO  
CON DADO FRESATO

*JOINT WITH MILLED NUT*



**ART. 23F**

INNESTO ATTACCO FILETTO  
MASCHIO TENUTA CON OR

*MALE JOINT SEAL  
WITH OR*




FILETTO / THREAD

1/4

**ART. 23D**

INNESTO ATTACCO A BAIONETTA

*BAYONET JOINT*



MOTO GUZZI V 500 cc.

PORTATA ARIA / AIR FLOW: 2000 l/min  
 PRESSIONE ARIA / MAX PRESSURE: 12 bar  
 TEMPERATURA / TEMPERATURE: -18 °C ÷ +80 °C

## ART. 200



RUBINETTO RAPIDO A SFERA  
 UNIVERSALE ATTACCO FILETTO  
 MASCHIO

UNIVERSAL QUICK BALL COUPLER  
 WITH MALE THREAD

FILETTO / THREAD

1/8
1/4
3/8
1/2

## ART. 210



RUBINETTO RAPIDO A SFERA  
 UNIVERSALE ATTACCO FILETTO  
 FEMMINA

UNIVERSAL QUICK BALL COUPLER  
 WITH FEMALE THREAD

FILETTO / THREAD

1/8
1/4
3/8
1/2

## ART. 220



RUBINETTO RAPIDO A SFERA  
 UNIVERSALE ATTACCO PORTAGOMMA

UNIVERSAL QUICK BALL COUPLER  
 FOR RUBBER HOSE

Ø	Ø	Ø
6x10	7x16	8x17
6x12	8x12	10x15
6x13	8x13	10x17
6x14	8x15	10x19

## ART. 230



RUBINETTO RAPIDO A SFERA  
 UNIVERSALE ATTACCO TUBO SPIRALE

UNIVERSAL QUICK BALL COUPLER  
 FOR SPIRAL HOSE

Ø	Ø
4x6	8x10
5x8	8x12
6x8	10x12
6,5x10	

## ART. 240



RUBINETTO RAPIDO A SFERA  
 UNIVERSALE ATTACCO PORTAGOMMA

UNIVERSAL QUICK BALL COUPLER  
 FOR RUBBER HOSE

Ø	Ø	Ø
6	9	12
7	10	13
8	11	14



ITALY TYPE



I

GERMANY TYPE



D

AMERICAN TYPE



USA

SWISS TYPE



CH

RUBINETTI UNIVERSALI PATENTED · UNIVERSAL SNAP COUPLING PATENTED

PORTATA ARIA / AIR FLOW: 2000 l/min  
 PRESSIONE ARIA / MAX PRESSURE: 12 bar  
 TEMPERATURA / TEMPERATURE: -18 °C ÷ +80 °C

## ART. 200Z

RUBINETTO RAPIDO A SFERA  
 UNIVERSALE ATTACCO FILETTO  
 MASCHIO GHIERA ZAMA  
*UNIVERSAL QUICK BALL COUPLER  
 WITH MALE THREAD ZAMA NUT*



FILETTO / THREAD
1/8
1/4
3/8
1/2

## ART. 210Z

RUBINETTO RAPIDO A SFERA  
 UNIVERSALE ATTACCO FILETTO  
 FEMMINA GHIERA ZAMA  
*UNIVERSAL QUICK BALL COUPLER  
 WITH FEMALE THREAD ZAMA NUT*



FILETTO / THREAD
1/8
1/4
3/8
1/2

## ART. 220Z

RUBINETTO RAPIDO A SFERA  
 UNIVERSALE ATTACCO PORTAGOMMA  
 GHIERA ZAMA  
*UNIVERSAL QUICK BALL COUPLER  
 FOR RUBBER HOSE ZAMA NUT*



Ø	Ø	Ø
6x10	7x16	8x17
6x12	8x12	10x15
6x13	8x13	10x17
6x14	8x15	10x19

## ART. 230Z

RUBINETTO RAPIDO A SFERA  
 UNIVERSALE ATTACCO TUBO SPIRALE  
 GHIERA ZAMA  
*UNIVERSAL QUICK BALL COUPLER  
 FOR SPIRAL HOSE ZAMA NUT*



Ø	Ø
4x6	8x10
5x8	8x12
6x8	10x12
6,5x10	

## ART. 240Z

RUBINETTO RAPIDO A SFERA  
 UNIVERSALE ATTACCO PORTAGOMMA  
 GHIERA ZAMA  
*UNIVERSAL QUICK BALL COUPLER  
 FOR RUBBER HOSE ZAMA NUT*



Ø	Ø	Ø
6	9	12
7	10	13
8	11	14

### ITALY TYPE




### GERMANY TYPE



### AMERICAN TYPE



### SWISS TYPE





PORTATA ARIA / AIR FLOW: 2000 l/min  
 PRESSIONE ARIA / MAX PRESSURE: 12 bar  
 TEMPERATURA / TEMPERATURE: -18 °C ÷ +80 °C

## ART. 200P

RUBINETTO RAPIDO A SFERA  
 UNIVERSALE ATTACCO FILETTO  
 MASCHIO GHIERA NYLON  
*UNIVERSAL QUICK BALL COUPLER  
 WITH MALE THREAD NYLON NUT*



FILETTO / THREAD
1/8
1/4
3/8
1/2

## ART. 210P

RUBINETTO RAPIDO A SFERA  
 UNIVERSALE ATTACCO FILETTO  
 FEMMINA GHIERA NYLON  
*UNIVERSAL QUICK BALL COUPLER  
 WITH FEMALE THREAD NYLON NUT*



FILETTO / THREAD
1/8
1/4
3/8
1/2

## ART. 220P

RUBINETTO RAPIDO A SFERA  
 UNIVERSALE ATTACCO PORTAGOMMA  
 GHIERA NYLON  
*UNIVERSAL QUICK BALL COUPLER  
 FOR RUBBER HOSE NYLON NUT*



Ø	Ø	Ø
6x10	7x16	8x17
6x12	8x12	10x15
6x13	8x13	10x17
6x14	8x15	10x19

## Art. 230P

RUBINETTO RAPIDO A SFERA  
 UNIVERSALE ATTACCO TUBO SPIRALE-  
 GHIERA NYLON  
*UNIVERSAL QUICK BALL COUPLER  
 FOR SPIRAL HOSE NYLON NUT*



Ø	Ø
4x6	8x10
5x8	8x12
6x8	10x12
6,5x10	

## ART. 240P

RUBINETTO RAPIDO A SFERA  
 UNIVERSALE ATTACCO PORTAGOMMA  
 GHIERA NYLON  
*UNIVERSAL QUICK BALL COUPLER  
 FOR RUBBER HOSE NYLON NUT*



Ø	Ø	Ø
6	9	12
7	10	13
8	11	14



### ITALY TYPE



I

### GERMANY TYPE



D

### AMERICAN TYPE



USA

### SWISS TYPE



CH

PORTATA ARIA / AIR FLOW: 2000 l/min  
 PRESSIONE ARIA / MAX PRESSURE: 12 bar  
 TEMPERATURA / TEMPERATURE: -18 °C ÷ +80 °C

## ART. 400



RUBINETTO RAPIDO UNIVERSALE  
 CON SICUREZZA  
 ATTACCO FILETTO FEMMINA  
*UNIVERSAL QUICK COUPLER  
 WITH SAFETY FEMALE THREAD*

FILETTO / THREAD

1/4
3/8
1/2

## ART. 401



RUBINETTO RAPIDO UNIVERSALE  
 CON SICUREZZA  
 ATTACCO FILETTO MASCHIO  
*UNIVERSAL QUICK COUPLER  
 WITH SAFETY MALE THREAD*

FILETTO / THREAD

1/4
3/8
1/2

## ART. 402



RUBINETTO RAPIDO UNIVERSALE  
 CON SICUREZZA  
 ATTACCO PORTAGOMMA  
*UNIVERSAL QUICK COUPLER  
 WITH SAFETY FOR RUBBER HOSE*

Ø

6x14
8x17
10x19

## ART. 403



RUBINETTO RAPIDO UNIVERSALE  
 CON SICUREZZA  
 ATTACCO PER TUBO SPIRALE  
*UNIVERSAL QUICK COUPLER  
 WITH SAFETY FOR SPIRAL HOSE*

Ø

Ø	Ø
4x6	8x10
5x8	8x12
6x8	10x12
6,5x10	

## ART. 404



RUBINETTO RAPIDO UNIVERSALE  
 CON SICUREZZA  
 ATTACCO PORTAGOMMA  
*UNIVERSAL QUICK COUPLER  
 WITH SAFETY FOR RUBBER HOSE*

Ø

Ø	Ø	Ø
6	9	12
7	10	13
8	11	14



ITALY TYPE




GERMANY TYPE



AMERICAN TYPE



SWISS TYPE



ARIA CHIUSA / AIR CLOSED




ARIA APERTA / AIR OPEN



SGANCIA INNESTO  
 QUICK DISCONNECT  
 COUPLING

PORTATA ARIA / AIR FLOW:  
 PRESSIONE ARIA / MAX PRESSURE:  
 TEMPERATURA / TEMPERATURE:

2000 l/min  
 12 bar  
 -18 °C ÷ +80 °C



RUBINETTI RAPIDI E RACCORDI TIPO TEDESCO · QUICK COUPLERS AND CONNECTORS GERMAN TYPE

**ART. 123**

RUBINETTO RAPIDO A SFERA  
 ATTACCO FILETTO MASCHIO

QUICK BALL COUPLER  
 MALE THREAD



FILETTO / THREAD
1/8
1/4
3/8
1/2

**ART. 120**

INNESTO ATTACCO FILETTO  
 MASCHIO

CONNECTION WITH MALE THREAD  
 FILETTO / THREAD



1/8
1/4
3/8
1/2

DISPONIBILI ANCHE IN VERSIONE TEMPERATA  
 AVAILABLE ALSO IN TEMPERED VERSION

**ART. 122**

RUBINETTO RAPIDO A SFERA  
 ATTACCO FILETTO FEMMINA

QUICK BALL COUPLER  
 FEMALE THREAD



FILETTO / THREAD
1/4
3/8
1/2

**ART. 121**

INNESTO ATTACCO FILETTO  
 FEMMINA

CONNECTION WITH FEMALE THREAD



FILETTO / THREAD
1/4
3/8
1/2

DISPONIBILI ANCHE IN VERSIONE TEMPERATA  
 AVAILABLE ALSO IN TEMPERED VERSION

**ART. 128**

RUBINETTO RAPIDO A SFERA  
 ATTACCO PORTAGOMMA

QUICK BALL COUPLER  
 RUBBER HOSE JOINT



Ø	Ø
6x10	8x12
6x12	8x15
6x14	8x17
7x16	10x19

**ART. 129**

INNESTO ATTACCO PORTAGOMMA

CONNECTION FOR RUBBER HOSE



Ø	Ø
6x10	8x12
6x12	8x15
6x14	8x17
7x16	10x19

**ART. 127**

RUBINETTO RAPIDO A SFERA  
 ATTACCO PER TUBO SPIRALE

QUICK BALL COUPLER  
 FOR SPIRAL HOSE



Ø	Ø
4x6	8x10
5x8	8x12
6x8	10x12
6,5x10	

**ART. 126**

INNESTO ATTACCO PER TUBO  
 SPIRALE

CONNECTION FOR SPIRAL HOSE



Ø	Ø
4x6	8x10
5x8	8x12
6x8	10x12
6,5x10	

**ART. 124**

RUBINETTO RAPIDO A SFERA  
 ATTACCO PORTAGOMMA

QUICK BALL COUPLER  
 FOR RUBBER HOSE



Ø	Ø	Ø
6	9	12
7	10	13
8	11	14

**ART. 125**

INNESTO ATTACCO PORTAGOMMA

CONNECTION FOR RUBBER HOSE



Ø	Ø
6	10
7	11
8	12
9	13
	14

## ART. 23A

INNESTO RAPIDO  
CON DADO FRESATO

*JOINT WITH MILLED NUT*



## ART. 129A

INNESTO BAIONETTA

*BAYONET CONNECTION*



## ART. 120A

INNESTO RAPIDO FILETTO  
MASCHIO TENUTA CON OR

*MALE JOINT SEAL WITH OR*




FILETTO / THREAD

1/4



MOTO MORINI 175 cc COMPETIZIONE

PORTATA ARIA / AIR FLOW: 1600 l/min  
 PRESSIONE ARIA / MAX PRESSURE: 12 bar  
 TEMPERATURA / TEMPERATURE: -18 °C ÷ +80 °C



RUBINETTI RAPIDI E RACCORDI TIPO SVIZZERO • QUICK COUPLERS AND CONNECTORS SWISS TYPE

## ART. 133

RUBINETTO RAPIDO A SFERA  
 ATTACCO FILETTO MASCHIO

QUICK BALL COUPLER  
 MALE THREAD



FILETTO / THREAD
1/4
3/8
1/2

## ART. 130

INNESTO ATTACCO  
 FILETTO MASCHIO

CONNECTION WITH  
 MALE THREAD



FILETTO / THREAD
1/4
3/8
1/2

## ART. 132

RUBINETTO RAPIDO A SFERA  
 ATTACCO FILETTO FEMMINA

QUICK BALL COUPLER  
 FEMALE THREAD




FILETTO / THREAD
1/4
3/8
1/2

## ART. 131

INNESTO ATTACCO  
 FILETTO FEMMINA

CONNECTION WITH  
 FEMALE THREAD




FILETTO / THREAD
1/4
3/8
1/2

## ART. 138

RUBINETTO RAPIDO A SFERA  
 ATTACCO PORTAGOMMA

QUICK BALL COUPLER FOR  
 RUBBER HOSE



Ø	Ø
6x10	8x12
6x12	8x17
6x14	10x19

## ART. 139

INNESTO ATTACCO PORTAGOMMA

CONNECTION FOR RUBBER HOSE



Ø	Ø
6x10	8x12
6x12	8x17
6x14	10x19

## ART. 137

RUBINETTO RAPIDO A SFERA  
 ATTACCO PER TUBO SPIRALE

QUICK BALL COUPLER  
 FOR SPIRAL HOSE



Ø	Ø
4x6	8x10
5x8	8x12
6x8	10x12
6,5x10	

## ART. 136

INNESTO ATTACCO  
 PER TUBO SPIRALE

CONNECTION  
 FOR SPIRAL HOSE



Ø	Ø
4x6	8x10
5x8	8x12
6x8	10x12
6,5x10	

## ART. 134

RUBINETTO RAPIDO A SFERA  
 ATTACCO PORTAGOMMA

QUICK BALL COUPLER  
 FOR RUBBER HOSE



Ø	Ø	Ø
6	9	12
7	10	13
8	11	

## ART. 135


INNESTO ATTACCO PORTAGOMMA

CONNECTION FOR RUBBER HOSE



Ø	Ø
6	10
7	12
8	13
9	

PORTATA ARIA / AIR FLOW: 1600 l/min  
 PRESSIONE ARIA / MAX PRESSURE: 12 bar  
 TEMPERATURA / TEMPERATURE: -18 °C ÷ +80 °C



## ART. 143

RUBINETTO RAPIDO A SFERA  
ATTACCO FILETTO MASCHIO

QUICK BALL COUPLER  
MALE THREAD



FILETTO / THREAD
1/4
3/8
1/2

## ART. 140

INNESTO ATTACCO FILETTO  
MASCHIO

CONNECTION WITH MALE THREAD



FILETTO / THREAD
1/4
3/8
1/2

## ART. 142

RUBINETTO RAPIDO A SFERA  
ATTACCO FILETTO FEMMINA

QUICK BALL COUPLER  
FEMALE THREAD




FILETTO / THREAD
1/4
3/8
1/2

## ART. 141

INNESTO ATTACCO FILETTO  
FEMMINA

CONNECTION WITH  
FEMALE THREAD




FILETTO / THREAD
1/4
3/8
1/2

## ART. 148

RUBINETTO RAPIDO A SFERA  
ATTACCO PORTAGOMMA

QUICK BALL COUPLER FOR  
RUBBER HOSE



∅	∅
6x10	8x12
6x12	8x17
6x14	10x19

## ART. 149

INNESTO ATTACCO PORTAGOMMA

CONNECTION FOR RUBBER HOSE



∅	∅
6x10	8x12
6x12	8x17
6x14	10x19

## ART. 147

RUBINETTO RAPIDO A SFERA  
ATTACCO PER TUBO SPIRALE

QUICK BALL COUPLER  
FOR SPIRAL HOSE



∅	∅
4x6	8x10
5x8	8x12
6x8	10x12
6,5x10	

## ART. 146

INNESTO ATTACCO  
PER TUBO SPIRALE

CONNECTION FOR SPIRAL HOSE



∅	∅
4x6	8x10
5x8	8x12
6x8	10x12
6,5x10	

## ART. 144

RUBINETTO RAPIDO A SFERA  
ATTACCO PORTAGOMMA

QUICK BALL COUPLER  
FOR RUBBER HOSE



∅	∅
6	10
7	12
8	13
9	

## ART. 145

INNESTO ATTACCO PORTAGOMMA


CONNECTION FOR RUBBER HOSE



∅	∅
6	10
7	12
8	13
9	

PORTATA ARIA / AIR FLOW:  
 PRESSIONE ARIA / MAX PRESSURE:  
 TEMPERATURA / TEMPERATURE:

2000 l/min  
 12 bar  
 -18 °C ÷ +80 °C



## ART. 170

RUBINETTO RAPIDO A SFERA  
 ATTACCO FILETTO MASCHIO

QUICK BALL COUPLER  
 WITH MALE THREAD



FILETTO / THREAD
1/4
3/8
1/2

## ART. 173

INNESTO ATTACCO  
 FILETTO MASCHIO

CONNECTION WITH  
 MALE THREAD



FILETTO / THREAD
1/4
3/8
1/2

## ART. 171

RUBINETTO RAPIDO A SFERA  
 ATTACCO FILETTO FEMMINA

QUICK BALL COUPLER  
 WITH FEMALE THREAD



FILETTO / THREAD
1/4
3/8
1/2

## ART. 174

INNESTO ATTACCO  
 FILETTO FEMMINA

CONNECTION WITH  
 FEMALE THREAD



FILETTO / THREAD
1/4
3/8
1/2

## ART. 172

RUBINETTO RAPIDO A SFERA  
 ATTACCO PORTAGOMMA

QUICK BALL COUPLER  
 FOR RUBBER HOSE



Ø
8
10
12

## ART. 175

INNESTO ATTACCO PORTAGOMMA

CONNECTION FOR RUBBER HOSE



Ø
8
10
12



RUBINETTI RAPIDI E RACCORDI TIPO NITTO (GIAPPONE) • QUICK COUPLERS AND CONNECTORS NITTO TYPE (JAPAN)

MOTO GUZZI SPORT 13 500 cc.



## ART. 27V



A

VALVOLA DI RITEGNO SVASATA ESTERNO

NON RETARD VALVE

FILETTO / THREAD

A	B
3/8	3/8
1/2	3/8
1/2	1/2
3/4	3/4
1"	1"

## ART. 27VM



A

VALVOLA DI RITEGNO SVASATA ESTERNO

NON RETARD VALVE

FILETTO / THREAD

A	B
3/8	3/8
1/2	3/8
1/2	1/2
3/4	1/2
1"	3/4

## ART. 27VD



A

VALVOLA DI RITEGNO DADO E OGIVA

NON RETARD VALVE NUT AND OGIVE

FILETTO / THREAD

A	Ø B
1/2	10
1/2	14

## ART. 27VDM



A

VALVOLA DI RITEGNO DADO E OGIVA

NON RETARD VALVE NUT AND OGIVE

FILETTO / THREAD

A	Ø B
1/2	10
3/4	14

## ART. 27S



VALVOLA DI SICUREZZA NON OMOLOGATA (SPECIFICARE TARATURA)

CALIBRATE SAFETY VALVE NOT APPROVED (SPECIFY CALIBRATION)

FILETTO / THREAD

1/4
3/8
1/2

## ART. 27SCE



VALVOLA DI SICUREZZA OMOLOGATA SECONDO DIRETTIVA 2014/68/EU (SPECIFICARE TARATURA)

CALIBRATE SAFETY VALVE APPROVED ACCORDING TO THE DIRECTIVE 2014/68/UE (SPECIFY CALIBRATION)

FILETTO / THREAD

1/4
3/8
1/2
3/4

## ART. 27S/A



VALVOLA DI SICUREZZA NON OMOLOGATA (SPECIFICARE TARATURA)

CALIBRATE SAFETY VALVE NOT APPROVED (SPECIFY CALIBRATION)

FILETTO / THREAD

1/4
3/8
1/2

## ART. 27VS



VALVOLA DI SPUNTO DI PARTENZA CHIUDE A 1 BAR

VALVE DEPARTURE CLOSE 1 BAR

FILETTO / THREAD

3/8
-----

## ART. 58NP



NIPPO 3 PEZZI ORIENTABILE ADJUSTABLE NIPPLE 3 PIECES

FILETTO / THREAD

1/4 x 3/8
-----------

## ART. 27VR



PASTIGLIA PER VALVOLE DI RITEGNO PAD FOR NON RETURN VALVE

Ø 15,6 x 10 NBR
Ø 15,6 x 10 VITON
Ø 16,9 x 10,5 NBR
Ø 16,9 x 10,5 VITON
Ø 23 x 12,5 VITON
Ø 29 x 15,5 VITON



## ART. 300

PRESSOSTATO MONOFASE

SINGLEPHASE PRESSURE SWITCH



VIE WAYS	FILETTO THREAD	PRESSIONE MAX MAX PRESSURE	AMP. MAX
4	1/4	12 bar	20

## ART. 310

PRESSOSTATO TRIFASE

THREEPHASE PRESSURE SWITCH



VIE	FILETTO THREAD	PRESSIONE MAX MAX PRESSURE	AMP. MAX
4	1/4	12 bar	20

## ART. 320

TELEPRESSOSTATO TRIFASE 1/4  
CON SALVAMOTORE INCORPORATO


THREEPHASE PRESSURE SWITCH  
WITH INTEGRATED OVERLOAD PROTECTION



VIE WAYS	FILETTO THREAD	PRESSIONE MAX MAX PRESSURE	AMP. MAX
4	1/4	12 bar	2/4
			4/6,3
			6,3/10
			10/16
			13/18
17/23			

# ART. 350

## RIPARTITORI IN ALLUMINIO ALUMINIUM MANIFOLDS



A"	B	C	D	E
G1/8	17	25	16	4,5
G1/4	21	30	18	4,25
G3/8	30	40	20	5,25
G1/2	37	50	30	6,5


# ART. 360

## RIPARTITORE USCITE MULTIPLE DA 1 LATO MANIFOLDS 1 SIDE OUTPUT



### ART. 360 2/2


#### 2 ENTRATE 2 USCITE / 2 INLETS 2 OUTLETS




A"	B"	D	E	F	G	H	L	M	K
G1/8	M5	15	15	45	22,5	3,5	20	15	4,25
G1/4	G1/8	15	30	60	30	4,5	30	20	5,25
G3/8	G1/8	18	30	66	33	4,5	40	20	5,25
G3/8	G1/4	18	36	72	36	6	40	20	6,5
G1/2	G1/4	22	36	80	40	6	40	28	6,5
G1/2	G3/8	25	40	90	45	6	40	28	6,5
G1/2	G1/2	30	40	100	50	6	40	28	6,5

### ART. 360 2/3

#### 2 ENTRATE 3 USCITE / 2 INLETS 3 OUTLETS




A"	B"	D	E	F	G	H	L	M	K
G1/8	M5	15	15	60	22,5	3,5	20	15	4,25
G1/4	G1/8	15	30	90	30	4,5	30	20	5,25




A"	B"	D	E	F	G	H	L	M	K
G3/8	G1/8	18	30	96	33	4,5	30	20	5,25
G3/8	G1/4	18	36	108	36	6	30	20	6,5
G1/2	G1/4	22	36	116	40	6	40	28	6,5
G1/2	G3/8	25	40	130	45	6	40	28	6,5
G1/2	G1/2	30	40	140	50	6	40	28	6,5

**ART. 360 2/4**

**2 ENTRATE 4 USCITE / 2 INLETS 4 OUTLETS**




A"	B"	D	E	F	G	H	L	M	K
G1/8	M5	15	15	75	22,5	3,5	20	15	4,25
G1/4	G1/8	15	30	120	30	4,5	30	20	5,25




A"	B"	D	E	F	G	H	L	M	K
G3/8	G1/8	18	30	126	33	4,5	30	20	5,25
G3/8	G1/4	18	36	144	36	6	30	20	6,5
G1/2	G1/4	22	36	152	40	6	40	28	6,5
G1/2	G3/8	25	40	170	45	6	40	28	6,5
G1/2	G1/2	30	40	180	50	6	40	28	6,5

**ART. 360 2/5**

**2 ENTRATE 5 USCITE / 2 INLETS 5 OUTLETS**




A"	B"	D	E	F	G	H	L	M	K
G1/8	M5	15	15	90	22,5	3,5	20	15	4,25
G1/4	G1/8	15	30	150	30	4,5	30	20	5,25




A"	B"	D	E	F	G	H	L	M	K
G3/8	G1/8	18	30	156	33	4,5	30	20	5,25
G3/8	G1/4	18	36	180	36	6	30	20	6,5
G1/2	G1/4	22	36	188	40	6	40	28	6,5
G1/2	G3/8	25	40	210	45	6	40	28	6,5
G1/2	G1/2	30	40	220	50	6	40	28	6,5

**ART. 360 2/6**

**2 ENTRATE 6 USCITE / 2 INLETS 6 OUTLETS**



A"	B"	D	E	F	G	H	L	M	K
G1/8	M5	15	15	105	22,5	3,5	20	15	4,25
G1/4	G1/8	15	30	180	30	4,5	30	20	5,25



A"	B"	D	E	F	G	H	L	M	K
G3/8	G1/8	18	30	186	33	4,5	30	20	5,25
G3/8	G1/4	18	36	216	36	6	30	20	6,5
G1/2	G1/4	22	36	224	40	6	40	28	6,5
G1/2	G3/8	25	40	250	45	6	40	28	6,5
G1/2	G1/2	30	40	260	50	6	40	28	6,5

## ART. 6B

ROTOLO TUBO GOMMA

RUBBER HOSE ROLLS



MT	Ø
100	6x12
	6x14
	8x17

## ART. 6C

ROTOLO TUBO NYLON "PA6"

NYLON HOSE "PA6" ROLLS



MT	Ø
100	4x6
	6x8
	8x10
	10x12

## ART. 6D

ROTOLO TUBO "RILSAN" "PA12"

Disponibili nei colori:  
NERO - NEUTRO - AZZURRO - BLU - GIALLO  
ROSSO

"RILSAN" HOSE "PA12" ROLLS

Available in: BLACK - NEUTRAL - LIGHT BLUE  
BLUE - YELLOW - RED



MT	Ø
100	2,5x4 - 4x6
	6x8 - 8x10
	10x12
50	12,5x15

## ART. 25RI

SPIRALE RACCORDATA  
RUBINETTO RAPIDO  
UNIVERSALE E INNESTO\*

SPIRAL HOSE WITH UNIVERSAL  
QUICK COUPLER AND CONNECTION\*



MT	Ø
4	6x8 - 8x10
7,5	6x8 - 8x10
10	6x8 - 8x10
15	6x8 - 8x10
30	6x8 - 8x10

\*SPECIFICARE TIPO DI INNESTO  
\*SPECIFY TYPE OF COUPLING

## ART. 25S

SPIRALE "RPL"

"RPL" SPIRAL HOSE



MT	Ø
30	4x6
	6x8
	8x10
	10x12

## ART. 25SR

SPIRALE "RILSAN"

"RILSAN" SPIRAL HOSE



MT	Ø
30	4x6
	6x8
	8x10
	10x12

## ART. 25PU

SPIRALE POLIURETANO

POLYURETHANE SPIRAL HOSE



MT	Ø
30	4x6
40	5x8
	6,5x10
	8x12

## ART. 00

SPIRALE "RPL"  
BAIONETTA-BAIONETTA RACCORDATA

BAYONET-BAYONET  
"RPL" SPIRAL HOSE



MT
4
7,5
10
15

## ART. 26PU

SPIRALE POLIURETANO RACCORDATA  
CON RUBINETTO RAPIDO UNIVERSALE  
E INNESTO\*

POLYURETHANE SPIRAL HOSE WITH  
UNIVERSAL QUICK COUPLER AND  
CONNECTION\*



MT	Ø
4	4x6 - 5x8
	6,5x10 - 8x12
8	4x6 - 5x8
	6,5x10 - 8x12
12	4x6 - 5x8
	6,5x10 - 8x12
17	4x6 - 5x8
	6,5x10 - 8x12

\*SPECIFICARE TIPO DI INNESTO  
\*SPECIFY TYPE OF COUPLING

## ART. 27PU

SPIRALE POLIURETANO

POLYURETHANE SPIRAL HOSE



MT	Ø
4	4x6 - 5x8
	6,5x10 - 8x12
8	4x6 - 5x8
	6,5x10 - 8x12
12	4x6 - 5x8
	6,5x10 - 8x12
17	4x6 - 5x8
	6,5x10 - 8x12

## CONDIZIONI GENERALI DI VENDITA


- Il presente catalogo annulla e sostituisce i precedenti. Con il conferimento dell'ordine si considerano accettate tutte le condizioni di vendita.
- La merce viaggia a rischio e pericolo del committente.
- Non si accettano reclami riflettenti imballi, spedizione, fatturazione, ecc., se non fatti entro 8 giorni dalla consegna della merce. Il prodotto è garantito, in linea con i nostri abituali canoni di qualità.
- I tempi di consegna non sono impegnativi, eventuali ritardi su parziale o totale consegna dell'ordinato, non possono dar luogo a nessuna rivalsa verso l'azienda O.M.G., salvo diversi accordi scritti e regolarmente accettati.
- Tutti i dati e le indicazioni tecniche citati nel presente catalogo non sono impegnativi e potranno essere modificati, in caso di necessità tecniche o produttive, senza alcun preavviso.
- Non si riconoscono pagamenti se non fatti contro nostra R.B., o rimesse dirette alla nostra sede.
- Per eventuali pagamenti effettuati oltre la scadenza pattuita, saranno addebitati interessi moratori al tasso corrente bancario.
- In caso di controversia è riconosciuta solo la competenza del Tribunale di Vicenza.

Questo catalogo è di proprietà esclusiva della ditta O.M.G. con sede in Brendola (VI). Senza il consenso della stessa ditta non può essere copiato né riprodotto, anche parzialmente, sotto pena delle sanzioni di legge in materia

## GENERAL SELLING CONDITIONS

- This catalog cancels and substitutes the previous one. Once the order is conferred all terms of sale are implicitly accepted.
- The goods are sent at the consumer's risk and peril.
- Complaints referring to packaging, mailing, invoicing etc., are accepted only if notified with 8 days from date of delivery. Regarding the quality of the goods it is always fully guaranteed by us.
- Date of delivery is never binding. Shortage of all or part of the goods on delivery can be claimed as redraft towards our firm only if accompanied by written terms agreed upon. Otherwise redraft cannot be claimed.
- All data and technical aspects cited in this price list are not binding and may be altered without notice due to technical or manufacturing necessities.
- Payment is accepted only if forwarded to our R.B. or by direct remittance to our office.
- As for payment forwarded after the agreed due date, moratorium interest will be debited into your current account.
- In case of controversy rights will be acknowledged by the Court of Vicenza.

This catalog is the exclusive property of the O.M.G. based in Brendola (VI). Without the consent of the Company may not be copied or reproduced, even partially, on pain of legal sanctions on





O.M.G. di Ghiotto Cav. Giuseppe & C. s.n.c.  
Via Pacinotti, 18 - 36040 Brendola (VI) ITALY  
tel/phone +39 0444 400671 - fax +39 0444 401025  
E-mail: [info@omgonline.it](mailto:info@omgonline.it)  
Web-site: [www.omgonline.it](http://www.omgonline.it)

